



APC SRVPM10KRIL uninterruptible power supply (UPS) Double-conversion (Online) 10 kVA 10000 W

Brand : APC

Product code: SRVPM10KRIL

Product name : SRVPM10KRIL




10 kVA, 10 kW, 220-240, 40/70Hz, 58 dB  
APC SRVPM10KRIL. UPS topology: Double-conversion (Online), Output power capacity: 10 kVA, Output power: 10000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 240 V. Form factor: Rackmount/Tower, Product colour: Black, Display type: LCD. Width: 438 mm, Depth: 615 mm, Height: 87 mm. Cables included: USB cable



| Features                        |                                                          | Battery                           |                                         |
|---------------------------------|----------------------------------------------------------|-----------------------------------|-----------------------------------------|
| UPS topology *                  | Double-conversion (Online)                               | Automatic battery test            | ✓                                       |
| Output power capacity *         | 10 kVA                                                   | Cold start                        | ✓                                       |
| Output power *                  | 10000 W                                                  | Design                            |                                         |
| Waveform *                      | Sine                                                     | Form factor *                     | Rackmount/Tower                         |
| Input operation voltage (min) * | 110 V                                                    | Product colour *                  | Black                                   |
| Input operation voltage (max) * | 300 V                                                    | Display type                      | LCD                                     |
| Input frequency *               | 40/70 Hz                                                 | LED indicators                    | ✓                                       |
| Output operation voltage (min)  | 220 V                                                    | Certification                     | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2 |
| Output operation voltage (max)  | 240 V                                                    | Operational conditions            |                                         |
| Surge energy rating             | 600 J                                                    | Operating temperature (T-T)       | 0 - 40 °C                               |
| Crest factor                    | 3:1                                                      | Operating relative humidity (H-H) | 0 - 95%                                 |
| ECO mode                        | ✓                                                        | Storage relative humidity (H-H)   | 0 - 95%                                 |
| Emergency Power Off (EPO)       | ✓                                                        | Operating altitude                | 0 - 3000 m                              |
| Noise level                     | 58 dB                                                    | Non-operating altitude            | 0 - 15000 m                             |
| Audible alarm(s)                | ✓                                                        | Weight & dimensions               |                                         |
| Audible alarm modes             | Alarm when on battery, Low battery alarm, Overload alarm | Width                             | 438 mm                                  |
| Auto-restart                    | ✓                                                        | Depth                             | 615 mm                                  |
| Ports & interfaces              |                                                          | Height                            | 87 mm                                   |
| USB port                        | ✓                                                        | Weight                            | 16 kg                                   |
| Serial interface                | ✓                                                        | Package width                     | 600 mm                                  |
| SmartSlot                       | ✓                                                        | Package depth                     | 760 mm                                  |
| Battery                         |                                                          | Package height                    | 240 mm                                  |
| Battery technology              | Sealed Lead Acid (VRLA)                                  | Package weight                    | 20 kg                                   |
| Battery voltage                 | 240 V                                                    | Packaging data                    |                                         |
| Hot-swap battery                | ✓                                                        | Cables included                   | USB cable                               |
|                                 |                                                          | Manual                            | ✓                                       |
|                                 |                                                          | Logistics data                    |                                         |
|                                 |                                                          | Harmonized System (HS) code       | 85078000                                |



0731304343837



731304343837

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-AUG-2024. Prints or copies of Information are only valid on the printed Publication date