

LG 55VH7J-H Signage Display Panorama design 139.7 cm (55") 700 cd/m 2 Full HD Black 24/7

Brand: LG Product code: 55VH7J-H

Product name: 55VH7J-H

- Brightness(Typ.): 700 nit

- Bezel : 1.74mm (Panel Bezel to Panel Bezel), 1.3mm (T/L), 0.44mm (B/R)

- Depth : 86.9 mm

- Interface : HDMI/ DP/ DVI-D/ USB/ RS232C/ RJ45/ Audio/ IR

55", 700 nits, 1920×1080 px, FHD, IPS, 100-240V, 50/60Hz, $1212.2 \times 683.0 \times 86.9$ mm, 18.8 kg LG 55VH7J-H. Product design: Panorama design. Display diagonal: 139.7 cm (55"), Display resolution: 1920×1080 pixels, Display brightness: 700 cd/m², HD type: Full HD. Operating hours (hours/days): 24/7.

Product colour: Black





Display		Design	
Panel type	IPS	VESA mounting *	✓
LED backlighting type	Direct-LED	Panel mounting interface	600 x 400 mm
Display diagonal * Display resolution *	139.7 cm (55") 1920 x 1080 pixels	Performance	
Display brightness *	700 cd/m ²	Purpose *	Commercial
HD type *	Full HD	On Screen Display (OSD)	✓
Touchscreen *	×	Operating hours (hours/days)	24/7
Native aspect ratio	16:9	Power	
Response time	8 ms	Power consumption (typical) *	250 W
Contrast ratio (typical)	1000:1	Power consumption (off)	0.5 W
Contrast ratio (dynamic)	500000:1	Energy efficiency class (SDR)	G
Viewing angle, horizontal Viewing angle, vertical	178° 178°	Energy consumption (SDR) per 100 hours	⁰ 157 kWh
Display number of colours	1.07 billion colours	AC input voltage	100-240 V
Rated lifetime	60000 h	AC input frequency	50/6 Hz
Native refresh rate	60 Hz	Energy efficiency scale	A to G
Haze rate	28%	Weight & dimensions	
Ports & interfaces		Display width	1212.2 mm
HDMI ports quantity *	2	Display depth	86.9 mm
HDMI version	2.2	Display height	683 mm
DVI port *	✓	Display weight	18.8 kg
DVI-D ports quantity	1	Packaging data	
DisplayPorts quantity *	1	Package width	1353 mm
USB port *	✓	Package depth	263 mm
USB ports quantity	1	Package height	855 mm
USB version Ethernet LAN *	2.0	Package weight	31 kg
	1	Packaging content	
Ethernet LAN (RJ-45) ports RS-232C	1 ✓	Remote control included	✓
	v	Cables included	DisplayPort, Power, RS-232
Design		Operational conditions	
Product design * Product colour *	Panorama design Black	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	10 - 80%





8806091407658

0195174014035



195174014035

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.