**EPSON**

# Epson EB-PQ2008W data projector 8000 ANSI lumens 3LCD 2160p (3840x2160) White

**Brand :** Epson

**Product name :** EB-PQ2008W

**Product code:** V11HB01980

- Patented 4K and imaging technology Outstanding 4K image quality delivers superb immersivity
- Ultra-compact and lightweight Small, powerful 8,000lm 4K projector
- Cross-platform lens compatibility Lets you build the optimal projection solution for every requirement
- Fit-and-forget reliability Up to 20,000 hours maintenance free
- Reduced environmental impact Energy-efficient with reduced requirements for packaging and transport 8000lm 4K projector

Epson EB-PQ2008W. Projector brightness: 8000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: 2160p (3840x2160). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Throw ratio: 0.34 - 7.16:1. Video colour modes: Cinema, Dynamic, Natural, Presentation. Serial interface type: RS-232C, Service port type: USB Type-B

## Projector

| | |
|---|---|
| Smart projector * | ✘ |
| Projector brightness * | 8000 ANSI lumens |
| Projection technology * | 3LCD |
| Projector native resolution * | 2160p (3840x2160) |
| Contrast ratio (typical) * | 5000000:1 |
| Native aspect ratio * | 16:9 |
| Number of colours | 1.07 billion colours |
| Keystone correction, horizontal | -30 - 30° |
| Keystone correction, vertical | -45 - 45° |
| Matrix size | 2.64 cm (1.04") |
| Heat dissipation | 1.707 BTU/h |

## Light source

| | |
|---|---|
| Light source type * | Laser |
| Service life of light source * | 20000 h |
| Service life of light source (economic mode) | 30000 h |

## Lens system

| | |
|---|---|
| Focus * | ✘ |
| Throw ratio | 0.34 - 7.16:1 |

## Video

| | |
|---|---|
| Analog signal format system * | Not supported |
| Full HD * | ✔ |
| 3D * | ✘ |
| Video colour modes | Cinema, Dynamic, Natural, Presentation |

## Ports & interfaces

| | |
|---|---|
| HDBaseT port | ✔ |
| Service port type | USB Type-B |
| USB 2.0 ports quantity * | 2 |
| USB 2.0 Type-A ports quantity | 2 |
| USB 2.0 Type-B ports quantity | 1 |
| Serial interface type * | RS-232C |
| HDMI ports quantity * | 3 |
| DVI port * | ✘ |

## Network

| | |
|---|---|
| Smart TV * | ✘ |
| Ethernet LAN * | ✔ |

## Storage

| | |
|---|---|
| Card reader integrated * | ✘ |

## Features

| | |
|---|---|
| Interactive * | ✘ |
| Noise level (economic mode) | 29 dB |
| On Screen Display (OSD) | ✔ |
| Noise level * | 35 dB |
| High Dynamic Range (HDR) supported | ✔ |
| High Dynamic Range (HDR) technology | High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG) |

## Design

| | |
|---|---|
| Market positioning * | Presentation |
| Product colour * | White |
| Placement | Ceiling, Desktop, Floor |
| Cable lock slot | ✔ |
| Cable lock slot type | Kensington |

## Display

| | |
|---|---|
| Built-in display * | ✘ |
| Colour depth | 10 bit |

## Power

| | |
|---|---|
| Power source * | AC |
| Power consumption (typical) * | 453 W |
| Power consumption (standby) * | 0.5 W |
| Power consumption (economy mode) | 410 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50/60 Hz |

## Operational conditions

| | |
|---|---|
| Storage temperature (T-T) | -10 - 60 °C |
| Operating relative humidity (H-H) | 20 - 80% |
| Storage relative humidity (H-H) | 10 - 90% |

## Weight & dimensions

| | |
|---|---|
| Width | 545 mm |
| Depth | 436 mm |
| Height | 189 mm |
| Weight * | 18.6 kg |

| Network | | Packaging content | |
| --- | --- | --- | --- |
| Ethernet LAN data rates | 10,100 Mbit/s | Remote control included * | ✔ |
| | | Batteries included | ✔ |

8715946718484