

# Eaton 5P1550IG2BS

Catalog Number: 5P1550IG2BS

Eaton 5P Gen2 UPS, 1550 VA, 1350 W, Input: C14, Outputs: (8) C13, Tower, BS Input cord

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton 5P Gen2 UPS	5P1550IG2BS
<b>EAN</b>	<b>Product Length/Depth</b>
3553340710452	445 mm
<b>Product Height</b>	<b>Product Width</b>
233 mm	150 mm
<b>Product Weight</b>	<b>Warranty</b>
15.36 kg	3 year on electronics, 2 year on battery
<b>Compliances</b>	<b>Certifications</b>
LVD Directive (CB)	IEC/EN 62040-1
EMC Directive	IEC/EN 62040-2
RoHS Directive	IEC/EN 62040-3
WEEE Directive	UL 1778
Packaging Directive	CSA-C22.2
Batteries Directive	CE
	UKCA
	Cm
	Ukr
	KCC
	cTUVus
	BIS

## Battery

### Runtime graph

\$row.attributeValue.cdata

### Battery type

Lead-acid maintenance-free (replaceable)

### Battery replacement

User replaceable

### Battery quantity

3

### Battery management

ABM or constant voltage charging method (user selectable),  
automatic battery test, deep discharge protection

### Battery rating

12 V / 9 Ah

### Extended battery capability

No

## Electrical output

### Voltage

230V

### Receptacle

(8) C13

### Wattage

1350 W

### Output voltage range

230 V (+6%/-10%)

### Output frequency

50/60 Hz

### Output nominal voltage

230V default (200/208/220/230/240V)

### Topology

Line-interactive

## Electrical input

### Input connection

C14

### Input nominal voltage

230V default (200/208/220/230/240V)

### Nominal frequency

50-60 Hz

### Input voltage range

160-294 V (adjustable to 150 V-294 V)

### Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in  
low sensitivity mode

## Communications

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for

remote On/Off and Remote

## Environmental

### Altitude

3000 m

### Noise level

<35 dB at 1 meter

### Temperature range

Power Off  
Dry contacts (2 outputs,  
optocoupler, RJ)

Ethernet interface

No

Potential free switch contact

Yes

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Brightlayer Software suite

Type of interface

Other

0° to 40°C (32° to 104°F)

BTU Rating

Online: 92, Battery: 654 BTU/hr

Relative humidity

0-90% non-condensing

Additional specifications

Form factor

Tower

Construction type

Free standing model

Enclosure

Black/silver

Package contents

- USB cable
- (2) IEC-IEC cables
- Quickstart guide
- Safety instructions

Phase (output)

1

Auto shutdown function

Yes

Color

Black/silver

Rack mounting kit

No

Efficiency

98,2

Phase (input)

1

Resources

Application notes

Runtime graph - 5P1550IG2

Brochures

Eaton 5P Gen2 UPS datasheet

## Declarations of conformity

[EU Declaration of conformity Eaton 5P Gen2 UPS](#)

## Manuals and user guides

[Eaton 5P Gen2 Tower - Advanced user guide](#)

[Eaton 5P Gen2 Quick Start Guide](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)