ATEN CS1764A KVM switch Black

Brand : ATEN

Product code: CS1764A

Product name : CS1764A

USB, DVI-I, 1920 x 1200 @ 60Hz, DDC2B, DC 5.3V, 10.7W, 940g

ATEN CS1764A. Keyboard port type: USB, Mouse port type: USB, Video port type: DVI-I. HD type: WUXGA, Maximum resolution: 1920 x 1200 pixels, Video bandwidth: 60 Hz. Product colour: Black, Housing material: Metal, LED indicators: USB, Yes. Power source: DC, Input voltage: 5.3 V, Power consumption (typical): 10.7 W. Compliance certificates: RoHS







Ports & interfaces		Display	
Number of computers controlled *	4	Built-in display *	×
Keyboard port type *	USB	On Screen Display (OSD)	×
Mouse port type * Video port type *	USB DVI-I	Power	
DVI-I ports quantity	5	Power source	DC
Console ports *	3.5mm headphone, 3.5mm mic, DVI-I, USB A	Input voltage Power consumption (typical)	5.3 V 10.7 W
Console USB ports quantity	2	System requirements	
USB hub	1	Windows operating systems	
USB 2.0 ports quantity	4	supported	1
USB connector type	USB Type-A	Linux operating systems supported	1
USB version	2.0	Mac operating systems supported	1
Audio connections	✓	Other operating systems supported	1
Headphone outputs	5	Sustainability	
Number of microphone inputs	5	Compliance certificates	RoHS
DC-in jack	 Image: A start of the start of		копо
		Operational conditions	
Performance		Operational conditions	
Performance HD type *	WUXGA	Operating temperature (T-T)	0 - 50 °C
HD type * Maximum resolution *	1920 x 1200 pixels	Operating temperature (T-T) Storage temperature (T-T)	-20 - 60 °C
HD type * Maximum resolution * Video bandwidth	1920 x 1200 pixels 60 Hz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	
HD type * Maximum resolution * Video bandwidth Scan interval	1920 x 1200 pixels 60 Hz 1,99 s	Operating temperature (T-T) Storage temperature (T-T)	-20 - 60 °C
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support	1920 x 1200 pixels 60 Hz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C
HD type * Maximum resolution * Video bandwidth Scan interval	1920 x 1200 pixels 60 Hz 1,99 s	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	-20 - 60 °C 0 - 80% 270 mm 88 mm
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support	1920 x 1200 pixels 60 Hz 1,99 s ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP	1920 x 1200 pixels 60 Hz 1,99 s ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	-20 - 60 °C 0 - 80% 270 mm 88 mm
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP Power on detection	1920 x 1200 pixels 60 Hz 1,99 s •	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm 940 g
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP Power on detection Firmware upgradeable	1920 x 1200 pixels 60 Hz 1,99 s •	Operating temperature (T-T)Storage temperature (T-T)Operating relative humidity (H-H)Weight & dimensionsWidthDepthHeightWeightPackaging contentCables included	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP Power on detection Firmware upgradeable Design	1920 x 1200 pixels 60 Hz 1,99 s •	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm 940 g
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP Power on detection Firmware upgradeable Design Product colour *	1920 x 1200 pixels 60 Hz 1,99 s ✓ ✓ ✓ ✓ ✓ ■ Black	Operating temperature (T-T)Storage temperature (T-T)Operating relative humidity (H-H)Weight & dimensionsWidthDepthHeightWeightPackaging contentCables included	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm 940 g DC, KVM
HD type * Maximum resolution * Video bandwidth Scan interval DDC2B support HDCP Power on detection Firmware upgradeable Design Product colour * Housing material	1920 x 1200 pixels 60 Hz 1,99 s ✓ ✓ ✓ ✓ ✓ ✓ Ølack Metal	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth Height Weight Packaging content Cables included Quick installation guide	-20 - 60 °C 0 - 80% 270 mm 88 mm 55.5 mm 940 g DC, KVM ✓











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.