

USB-C Multiport Adapter - 4K 60Hz HDMI - HDR - 2-Port 5Gbps USB 3.0 Hub - 100W Power Delivery Pass-Through - GbE - Works with Chromebook certified - Windows/macOS

Product ID: 103B-USBC-MULTIPORT



This Works With Chromebook (WWCB) certified USB-C Multiport Adapter supports up to 4K 60Hz HDMI 2.0b (HDR10) via DP Alt Mode. The USB-C dock converts a USB-C laptop or tablet, such as a Chromebook, Dell XPS, or a MacBook, into a workstation. The adapter connects to a host computer's USB-C, USB4, or Thunderbolt 3/4 port. It features one HDMI video output, a 2-Port USB 3.2 Gen 1 (5 Gbps) Hub, and Gigabit Ethernet. Connect a laptop USB-C power supply to the dedicated USB Power Delivery (PD) 3.0 port, located on the Multiport Adapter, to charge the laptop. The Multiport Adapter features an extra-long built-in 12-inch (30 cm) USB-C host cable.

This USB-C Multiport Adapter is tested and certified to meet Google's compatibility standards ensuring seamless operation with Chromebook devices. The Multiport Adapter is ideal for setup and deployment in Google environments. Automatic firmware updates are available through ChromeOS for maximum security, compatibility, and performance.

The USB-C to USB 3.2 Gen 1 hub features two 5Gbps USB Type-A ports, for connecting USB peripherals.

A versatile dock solution for use at your office, home office, hotel, or in the boardroom. It's portable enough to be carried in a bag or backpack. This lightweight USB-C Adapter can operate with bus-power alone, or use the dedicated USB-C Power Delivery port to connect a USB-C power adapter (not included with Multiport Adapter) for laptop charging.

Connect a USB-C power source (not included), such as the power adapter included with a laptop, to the USB-C Power Delivery pass-through port. With support for USB Power Delivery 3.0 pass-through (up to 100W), the USB Type-C Multiport Adapter allows you to power and charge your laptop. USB PD 3.0 features Fast Role Swap (FRS) to prevent USB data disruption when disconnecting the power source.

The Gigabit Ethernet port ensures reliable wired network access, with support for PXE Boot and Wake-on-LAN (WoL).

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that is compatible with a wide variety of IT connectivity accessories. The software suite includes:



Advanced Windows Layout Utility: Setup and save custom windows layouts.

MAC Address Pass-Through Utility: Improve network security.

USB Event Monitoring Utility: Track and log connected USB devices.

Wi-Fi Auto Switch Utility: Enable quick access to wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.startech.com/connectivity-tools

This product is backed for 3 years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility



















Applications

- Ideal for deployment in Google environments with automatic firmware updates available through ChromeOS
- Travel between the home and office

Features

- 5-IN-1 MULTIPORT ADAPTER: Portable USB-C travel dock supports 4K 60Hz HDMI 2.0b (HDR10) video via DP 1.4 Alt Mode for connecting a monitor/display, 2-port USB-A hub (2x USB 3.2 Gen 1 5Gbps), 100W USB-C Power Delivery Pass-Through, Gigabit Ethernet
- WORKS WITH CHROMEBOOK: WWCB certified for guaranteed compatibility with Chromebook devices; Auto firmware updates through ChromeOS for max performance, compatibility & security; Windows/macOS/iPadOS/Android/Ubuntu compatible
- EXTRA-LONG CABLE: Extended port reach w/attached 12" (30cm) host cable, clip for cable management, automatic driver setup, weighted design to keep adapter more stable on work surface, ideal for office or work-from-home workstations & presenting from a boardroom
- RELIABLE PERFORMANCE: 100W Power Delivery Pass-Through with 14W reserved for adapter (when using one or all ports) and up to 86W available for host laptop charging; Prevents device dropouts, video flickering, and/or power overdraw common in other hubs
- USB PORTS WITH DEDICATED POWER: Two downstream USB-A ports support USB 3.2 Gen 1 (5Gbps) and with a USB-C power adapter connected, each port provides 4.5W (5V/0.9A) of dedicated power, ideal for connecting USB



devices that require a consistent power draw

Hardware

Warranty 3 Years

4K Support Yes

Fast-Charge Port(s) No

Displays Supported 1

Interface USB 3.2 Gen 1 (5Gbps)

Bus Type USB-C

Industry Standards HDMI 2.0b

USB 3.2 Gen 1 (5Gbps)

USB Power Delivery Specification Rev. 3.0

Certified Works with ChromeBook (WWCB)

Chipset ID Realtek - RTL8153B

Analogix - ANX7327

Analogix - ANX7518

VIA - VL817-Q7

Performance

Maximum Data Transfer

Rate

5Gbps

Maximum Digital

Resolutions

Up to 4K (4096x2160) 60Hz

Type and Rate USB 3.2 Gen 1 - 5 Gbit/s

UASP Support Yes

Compatible Networks 10/100/1000 Mbps

PXE Yes

Full Duplex Support Yes

General Specifications Maximum Laptop Charging: 86W



Connector(s)

External Ports 1 - HDMI (19 pin)

2 - USB 3.2 Type-A (9 pin, Gen 1, 5Gbps)

1 - RJ-45

1 - USB Type-C (24 pin) USB Power Delivery Only

Host Connectors

1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)

Software

OS Compatibility Windows 10, 11
br / >macOS 10.15, 11.0, 12.0
br / >Android

<br / >Linux Ubuntu 18.04, 20.04<br / >ChromeOS (Certified)

Works with Chromebook)

Special Notes / Requirements

System and Cable Requirements

A host device with an available USB-C port (to ensure full adapter functionality, the host device's USB-C port must support

USB Power Delivery 2.0 and DP alt mode).

Optional: USB-C power adapter (for example, your laptop's

USB-C based power adapter).

Note Not all USB-C ports support the full functionality of the USB

Type-C standard. Ensure that your host USB-C port supports

USB Power Delivery and DP alt mode.

If the USB-C Host does not support USB Power Delivery, the PD

Power Port will not supply power to the USB-C Host.

A 4K-capable display is required to achieve UHD resolution (4K

is also known as 4K x 2K).

USB 3.2 Gen 1 (5Gbps) is also known as USB 3.1 Gen 1

(5Gbps) and USB 3.0 (5Gbps).

Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information

about Power Delivery, refer to the manufacturer of your

hardware.

Power

Power Source Bus Powered and Host USB-C Power Adapter

Power Delivery 100W



Power Consumption	(In	14W
147 44 1		

Watts)

Environmental

Operating Temperature 0C to 35C (32F to 95F)

Storage Temperature -25C to 65C (-13F to 149F)

Humidity 0~95% RH (Non-condensing)

Physical Characteristics

Color Space Gray

Material Plastic

Cable Length 11.8 in [30 cm]

Product Length 3.9 in [10.0 cm]

Product Width 1.9 in [4.8 cm]

Product Height 0.6 in [1.6 cm]

Weight of Product 3.7 oz [105.0 g]

Packaging Information

Package Length 7.1 in [18.0 cm]

Package Width 4.5 in [11.5 cm]

Package Height 1.6 in [4.0 cm]

Shipping (Package) 4.2 oz [120.0 g] Weight

What's in the Box

Included in Package 1 - USB-C Multiport Adapter

1 - Quick-Start Guide

^{*}Product appearance and specifications are subject to change without notice.