



APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT2200RMXLI-NC

Product name : Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit



Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit

APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit. UPS topology: Double-conversion (Online), Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 12 AC outlet(s), Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 367 VAh, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 584 mm, Height: 85 mm

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	2.2 kVA	Rack capacity	2U
Output power *	1980 W	Cable length	2.44 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	160 V	Display type	LCD
Input operation voltage (max) *	275 V	LED indicators	✓
Input frequency *	40 - 70 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Output operation voltage (max)	240 V	Operational conditions	
Surge energy rating	340 J	Operating temperature (T-T)	0 - 40 °C
Crest factor	3:1	Storage temperature (T-T)	-20 - 50 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	2%	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, C19 coupler	Sustainability certificates	ENERGY STAR, Green Premium
AC outlets quantity	12 AC outlet(s)	Compliance certificates	RoHS
Number of output IEC jumpers	2	Weight & dimensions	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	584 mm
Serial interface type	RJ-45	Height	85 mm
Ethernet LAN (RJ-45) ports	1	Weight	25 kg
SmartSlot	✓	Package width	599 mm
Battery		Package depth	810 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery capacity	367 VAh	Package weight	34 kg
Number of batteries supported	1	Logistics data	
Battery life (max)	5 year(s)	Harmonized System (HS) code	85078000
Battery recharge time	3 h	Other features	
		Output voltage	230 V



0731304327561



731304327561

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date