

RoboSHOT 20 UHD

HIGH PERFORMANCE, ULTRA HIGH DEFINITION PTZ CAMERA

Black

999-9950-000B (North America)
999-9950-001B (Europe/UK)
999-9950-009B (Australia/New Zealand)

White

999-9950-000W (North America)
999-9950-001W (Europe/UK)
999-9950-009W (Australia/New Zealand)

Silver/Black (Discontinued Color)

999-9950-000 (North America)
999-9950-001 (Europe/UK)
999-9950-009 (Australia/New Zealand)

FEATURES

- Back-illuminated 9.03 Megapixel, ultra high definition 1/2.3-type sensor delivers native 2160p/30 (3840 x 2160) video
- 12x optical zoom and 1.67x digital zoom; effective 20x zoom range; horizontal field of view 74° (wide) to 4.8° (tele) at 20x
- Imaging and performance comparable to 3-chip cameras
- Precise pan and tilt movements from 120° per second down to 0.35° per second
- Simultaneous HDMI, HDBT, 3Gb/s HD-SDI and IP streaming outputs
- Presenter-friendly IR remote control
- Full administrative control from your browser via web interface
- Integration-ready Telnet or serial RS-232 control
- Smooth, silent direct-drive motors



CONNECTOR PANEL

- **12 VDC, 3.0 Amp power connector** – Connect the power supply shipped with the camera
- **OneLINK/HDBT connector** – Connect to OneLINK interface (video, power and control up to 328 ft/100m)
- **HDMI connector** – HDMI video output
- **HD-SDI connector** – HD-SDI video output
- **RS-232 port** – Connect to a controller to manage the camera using a modified VISCA protocol
- **Camera Settings rotary switch** – Sets the video output resolution.



RoboSHOT 20 UHD

HIGH PERFORMANCE, ULTRA HIGH DEFINITION PTZ CAMERA

WHAT'S INCLUDED

Each RoboSHOT 20 UHD camera is shipped with these items:

- Vaddio IR Remote Commander
- Thin Profile Wall Mount with mounting hardware (black/white)
- 12 VDC, 3.0 A switching power supply and AC cord set(s)
- EZCamera™ RS-232 control adapter

SPECIFICATIONS

Video and Image

Outputs/protocols	HDMI, HDBT, HD-SDI, IP (H.264)	Aspect ratio	HDMI: 16:9 (all resolutions) IP (H.264) Streaming: 16:9, 3:2 and 4:3
HDMI resolutions/ frame rates resolutions/frame rates	QFHD: 2160p/30/25 (3840 x 2160) FHD: 1080p/59.94/50/29.97/25, 1080i/59.94/50 HD: 720p/59.94/50	3Gb/s HD-SDI resolutions/frame rates	FHD: 1080p/59.94/50/29.97/25, 1080i/59.94/50 HD: 720p/59.94/50
Streaming	Simultaneous IP (RTSP format with H.264 compression) up to 1080p/30		

Camera

Image device	1/2.3-Type Exmor R High-speed, Low-noise CMOS Sensor		
Pixels	9.03 Megapixels Total, 8.93 Effective Megapixels		
Zoom	12x optical zoom, 1.67x digital zoom; combined total 20x zoom		
Minimum illumination	3.0 lx (F1.8, 50IRE) color; recommended 100+ lux		
Horizontal FOV	74° (wide) to 4.8° (tele)	Min. working distance	10 mm (wide), 1500 mm (tele)
Pan angle and speed	±160°, 0.35°/sec to 120°/sec	Tilt angle and speed	±90°, -30°, 0.35°/sec to 120°/sec
Gain	Auto / Manual (0 to 33 dB)	Aperture/detail	16 Steps
Focusing system	Auto Focus / Manual Focus Mode / One Push Trigger Mode		
White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual		
Backlight compensation	On/off	Sync system	Internal
Noise reduction	6 steps	S/N ratio	Over 50 dB
Control and management	Vaddio IR Remote Commander, web interface (Chrome, Firefox, Safari, Internet Explorer, Microsoft Edge), Telnet, RS-232 API (modified VISCA)		
Power	12 VDC, 3.0 Amp power supply; LTPoE++		

Physical and Environmental

Height	7.9 in (200 mm)	Operating temperature	-5°C to + 60°C (23°F to 140°F)
Width	8.0 in (203 mm)	Operating humidity	20% to 80% RH (non-condensing)
Depth	7.7 in (196 mm)	Storage temperature	-20°C to + 60°C (-4°F to 140°F)
Weight	6 lbs (2.7 kg)	Storage humidity	20% to 95% RH (non-condensing)