Sony BRC-H800 Dome IP security camera Indoor Ceiling

Brand : Sony

Product code: BRC-H800W/AC

Product name : BRC-H800

BRC-H800, 1" Exmor R CMOS, 14.2 MP, 1080p, f 9.3-111.6 mm, F 2.8, F 4.5, 2x 3G-SDI, HDMI, RS-422, 198 x 260 x 238 mm, 4300 g, white, AC adapter

Sony BRC-H800. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Minimum illumination: 1.7 lx, Lens viewing angle, horizontal: 64.6°, Tilt angle range: -30 - 90°. Sensor type: CMOS, Optical sensor size: 25.4 / 0 mm (1 / 0"). Optical zoom: 12x, Focal length range: 9.3 - 111.6 mm, Focus: Motorized/Manual





Performance		Video	
Type * Placement supported * Connectivity technology * PTZ control	rement supported * Indoor Inectivity technology * Wired	Total megapixels * Supported video modes Gain control type Number of TV lines (horizontal)	20.4 MP 720p, 1080i, 1080p Auto/Manual 850
Preset points Day/night mode Light exposure modes Design	✓ ✓ Auto, Manual, Shutter priority AE	Network Ethernet LAN * Wi-Fi *	✓ ×
Form factor * Mounting type * Product colour *	Dome Ceiling White	Bluetooth * Storage Built-in HDD *	× ×
Camera Minimum illumination	1.7 lx	Ports & interfaces DC-in jack	1
Lens viewing angle, horizontal Tilt angle range	brizontal 64.6° -30 - 90° 60 °/sec -170 - 170° 60 °/sec Auto, Manual 1/10000s - 1/8 (59.94/29.97);	Interface Power	RJ-45/BNC
Tilt speed Pan range Pan speed White balance Camera shutter speed		Power source type * Power consumption (max) Power consumption (Power over Ethernet (PoE)) DC output voltage	DC, PoE 19 W 23 W 12
Image sensor	1/10000s - 1/6 (50/25/23.98)	Operational conditions	0 - 40 °C
Number of sensors Optical sensor size Sensor type *	1 25.4 / 0 mm (1 / 0") CMOS	Operating temperature (T-T) Storage temperature (T-T) Weight & dimensions	0 - 40 °C -20 - 60 °C

Lens system		Weight & dimensions	
Zoom capability	✓	Width	198 mm
Optical zoom	12x	Depth	238 mm
Number of lenses *		Height	260 mm
Focal length range		Weight	4.3 kg
Auto focus	✓ Motorized/Manual 4.5 2.8 0.08 m	Packaging content	
Focus		Number of cameras *	1
Maximum aperture number		Mounting kit	 Image: A set of the set of the
Minimum aperture number		AC adapter included	1
Closest focusing distance			-
		Logistics data	

Harmonized System (HS) code 85258900



5013493367593

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.