## **PHILIPS**

## Philips Evnia 5000 27M2N5500/00 LED display 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black

Brand : Philips Product family: Evnia Product code: 27M2N5500/00

Product name: 27M2N5500/00

Fast IPS Gaming monitor 27M2N5500 Quad HD gaming monitor

Philips Evnia 5000 27M2N5500/00 LED display 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black:

This monitor is equipped for any game. With its 0.5ms Smart MBR, 180Hz refresh rate, and Quad HD resolution, it is made to bring gamers an all-around and visually pleasing gaming experience. Philips Evnia 5000 27M2N5500/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Panel mounting interface	100 x 100 mm
Display resolution *	2560 x 1440 pixels	Cable lock slot *	<b>✓</b>
HD type *	Quad HD	Cable lock slot type	Kensington
Native aspect ratio *	16:9	Height adjustment *	✓
Display technology *	LCD	Height adjustment	13 cm
Panel type *	Nano IPS	Pivot	<b>✓</b>
LED backlight	✓		-90 - 90°
Backlight type	W-LED	Swivelling	<b>✓</b>
Touchscreen *	×	Swivel angle range	-45 - 45°
Display brightness (typical)	350 cd/m <sup>2</sup>	Tilt adjustment	1
Response time *	1 ms	Tilt angle range	-5 - 20°
Anti-glare screen	✓	On Screen Display (OSD)	✓ ·
Screen shape *	Flat	on sercen bisplay (63b)	Simplified Chinese, Traditional
Contrast ratio (typical) *  Dynamic contrast ratio marketing name  Maximum refresh rate *	1200:1 Mega Infinity DCR 170 Hz	On Screen Display (OSD) languages	Chinese, Czech, German, Dutch,
Viewing angle, horizontal	178°	Number of OSD languages	21
Viewing angle, vertical	178°	Plug and Play	✓
Display number of colours * Response time (fast)	1.07 billion colours 0.5 ms	LED indicators	Operation, Stand-by
Pixel pitch	0.2331 x 0.2331 mm	Power	
Pixel density	108.79 ppi	Power consumption (typical) *	29.8 W
Horizontal scan range	30 - 280 kHz	Power consumption (standby) *	0.5 W
Vertical scan range	48 - 180 Hz	Power consumption (off)	0.3 W
Viewable size, horizontal	59.7 cm	AC input voltage	100 - 240 V
Viewable size, vertical	33.6 cm	AC input frequency	50/60 Hz
Digital horizontal frequency	30 - 230 kHz	Power supply type	External
Digital vertical frequency	48 - 144 Hz	Operational conditions	
Display diagonal (metric)	68.5 cm	Operating temperature (T-T)	0 - 40 °C
High Dynamic Range (HDR) supported	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C 20 - 80%	

Display		Operational conditions	
High Dynamic Range (HDR)	DisplayHDR 400	Operating altitude	0 - 3658 m
technology		Non-operating altitude	3658 - 12192 m
DDC/CI	<b>✓</b>	Weight & dimensions	
Colour gamut standard DCI Colour gamut 93.s sRGB coverage (typical) 125	3H 8 bit DCI-P3 93.5% 125% 89%	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	614 mm 261 mm 519 mm 5.68 kg 614 mm 60 mm 368 mm 3.28 kg
Performance			5.20 kg
NVIDIA G-SYNC *  AMD FreeSync *  Fast charging	✓ ✓	Packaging data  Package width  Package depth  Package height	730 mm 188 mm 478 mm
Component video sync	Separate sync	Package weight	9.53 kg
Flicker-free technology  Low Blue Light technology	<b>v</b>	Packaging content	
	•	Stand included	<b>✓</b>
Multimedia		Cables included	AC, DisplayPort, HDMI
Built-in speaker(s) *	X	Sustainability	
Built-in camera *	×	Sustainability compliance	<b>✓</b>
Design		Doesn't contain	Mercury, PVC/BFR
Market positioning *	Gaming	Other features	
Product colour *	Black	Low input lag	✓
Ports & interfaces		Compatible operating systems	Mac OS X Windows 11/10
HDMI *	✓	Exterior finish type	Textured
HDMI ports quantity	2	Picture enhancement Recyclable packaging material	SmartImage game 100%
HDMI version DisplayPorts quantity DisplayPort version Headphone out *	2.0 1 1.4	Regulatory Approvals	CB, CCC, CECP, CEL, CE Mark, TUV-BAUART, EAC, MEPS, PSB, BSMI, EMF, FCC, ICES-003, TUV/ISO9241-307, UKCA
HDCP	✓	Heavy metals free	Hg (mercury)
HDCP version	1.4/2.2	Delta E	2
Ergonomics		Adaptive synchronisation	1
VESA mounting *	<b>✓</b>	EasyRead mode	<b>✓</b>
<b>.</b>		LowBlue mode	<b>/</b>
		Philips SmartUniformity Compliance certificates	93 - 105% RoHS
		Mean time between failures (MTBF)	



8712581809645

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.