

## Acer X1329 Standard throw projector 4800 ANSI lumens DLP WXGA (1280x800) Black

Brand : Acer Product code: MR.JX711.002

**Product name:** X1329

- 4800 Lumens Brightness
- WXGA Resolution
- Optional Dongle Wireless
- Acer ColorBoost3D
- Acer LumiSense
- Acer BlueLightShield
- Acer ColorSafe II
- Eco-Mode
- Integrated Speakers

DLP, 4800 lm, 1280x800, WUXGA, f/2.56, 16:10, 20.000:1, 1.07 Billion Colors Acer X1329. Projector brightness: 4800 ANSI lumens, Projection technology: DLP, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 5000 h, Service life of light source (economic mode): 10000 h. Focus: Manual, Focal length range: 22 - 24.1 mm, Aperture range (F-F): 2.56 - 2.68. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 1280 x 800 (WXGA), 1920 x 1200 (WUXGA). Serial interface type: RS-232





Projector		Ports & interfaces	
Projection distance 1 - 10 m Projector brightness * 4800 AN: Projection technology * DLP Projector native resolution * WXGA (1	4800 ANSI lumens DLP WXGA (1280x800)	PC Audio out VGA (D-Sub) ports quantity * HDMI ports quantity * Composite video in * DVI port *	1 2 1
Contrast ratio (typical) * Native aspect ratio * Number of colours Projector brightness (economic	20000:1 16:10 1.07 billion colours 3840 ANSI lumens	Network  Smart TV *  Ethernet LAN *	× ×
mode) Uniformity Horizontal scan range	85% 15 - 100 kHz	Wi-Fi * Features	×
Vertical scan range Keystone correction, vertical <b>Light source</b>	24 - 120 Hz -40 - 40°	Projection modes  Noise level *  Multimedia	Ceiling, Front, Rear 29 dB
Light source type * Service life of light source * Service life of light source (economic mode)	Lamp 5000 h 10000 h	Built-in speaker(s) * RMS rated power Number of built-in speakers	3 W 1
Lamp type	P-VIP	Design	
Lamp power Lamps quantity	203 W 1 lamp(s)	Market positioning * Product type *	Presentation Standard throw projector
Lens system Focus * Focal length range Aperture range (F-F)	Manual 22 - 24.1 mm 2.56 - 2.68	Product colour * Placement Cable lock slot Cable lock slot type	Black Ceiling
Zoom capability	<b>✓</b>	Display	
Zoom type	Manual	Built-in display *	×
Zoom ratio Offset	1.1:1 100%	Power Power source *	AC
Video		Power consumption (typical) *	260 W
Analog signal format system * Supported graphics resolutions	NTSC, PAL, SECAM 1280 x 800 (WXGA), 1920 x 1200 (WUXGA)	Power consumption (standby) * AC input voltage AC input frequency	0.5 W 120 - 230 V 50 Hz

Ports & interfaces		Operational conditions	
HDMI version USB 2.0 ports quantity USB 2.0 Type-A ports quantity Audio (L/R) in * Audio (L/R) out Serial interface type * PC Audio in	1.4 1 1 1 1 RS-232	Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	0 - 40 °C 0 - 90%
		Width Depth Height Weight *	299.5 mm 220 mm 105.1 mm 2.4 kg
		Packaging content	
		Remote control included *	✓
		Batteries included	✓
		Cables included	AC, VGA
		Carrying case	<b>✓</b>

