PHILIPS

Philips B Line 276B9H/00 LED display 68.6 cm (27") 2560 x 1440 pixels Quad HD Black

Brand : Philips Product family: B Line Product code: 276B9H/00

Product name: 276B9H/00

Business Monitor 276B9H LCD monitor with USB-C

Philips B Line 276B9H/00 LED display 68.6 cm (27") 2560 x 1440 pixels Quad HD Black:

The Philips B line monitor with USB-C replaces cable clutter. View Quad HD image quality and re-charge your laptop all at the same time with a single USB-C cable. A secure pop-up webcam with Windows Hello offers personalised, greater security.

Philips B Line 276B9H/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Pivot angle	-90 - 90°
Display resolution *	2560 x 1440 pixels	Swivelling	✓
HD type *	Quad HD	Swivel angle range	-175 - 175°
Native aspect ratio *	16:9	Tilt adjustment	✓
Display technology *	LED	Tilt angle range	-5 - 30°
Panel type *	IPS	On Screen Display (OSD)	✓
Backlight type	W-LED		Simplified Chinese, Traditional
Touchscreen *	×		Chinese, Czech, German, Dutch,
Display brightness (typical)	350 cd/m ²	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese,
Response time *	4 ms		Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display surface	Matt		
Anti-glare screen	✓	Number of OSD languages	21
Screen shape *	Flat	Plug and Play	✓
Aspect ratio	16:9	LED indicators	Operation, Stand-by
Contrast ratio (typical) *	1000:1	Power	
Contrast ratio (dynamic)	50000000:1	Energy efficiency class (SDR) *	F
Dynamic contrast ratio marketing name	SmartContrast	Energy consumption (SDR) per 1000 hours *	
Maximum refresh rate *	75 Hz	Power consumption (typical) *	18.6 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.3 W
Viewing angle, vertical	178°	Power consumption (off)	0 W
Display number of colours *	16.7 million colours	Power consumption (PowerSave)	14.9 W
Pixel pitch	0.233 x 0.233 mm	AC input voltage	100 - 240 V
Pixel density	109 ppi 30 - 114 kHz	AC input frequency	50 - 60 Hz
Horizontal scan range Vertical scan range	48 - 75 Hz	Power supply type	Internal
Viewable size, horizontal	46 - 73 п2 59.7 cm	Energy efficiency scale	A to G
Viewable size, riorizontal Viewable size, vertical Display diagonal (metric)	33.6 cm 68.6 cm	European Product Registry for Energy Labelling (EPREL) code	493899

DDC/CI Haze rate 25% Storage temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Operating relative humidity (H-H) Operating relative humidity (H-H) Operating altitude Operating al	Display		Operational conditions	
Surface handness		1		0 - 40 °C
Surface hardness	•		· -	
SRGE coverage (typical) 124% Operating altitude 0 - 3258 m NTSC coverage (typical) 111% Non-operating altitude 0 - 12192 m Display SRGE V Weight 6 dimensions Weight 6 dimensions Width (with stand) 253 mm NNDIA 6-SYNC* X Depth (with stand) 253 mm AND FreeSync* X Weight (with stand) 7.85 kg VESA Adaptive Sync support V Width (without stand) 614 mm Component video sync Separate sync Depth (with stand) 614 mm Circker-free technology V Height (without stand) 614 mm Low Bue Light technology V Height (without stand) 51 kg Multimedia V Packaging data 32 mm Number of speakers 2 Packaging width 690 mm RMS Tacto power 2 W Package weight 250 mm Built-in speaker(s)* - Package weight 103 kg Mustact power - W Package weight 103 kg Built-in speaker(s)* - Pac				
Non-operating altitude			•	
Performance			•	
Performance Wilth (with stand) 614 mm N/IDIA CSYNC* X Depth (with stand) 23 mm AMD FreeSync* X Height (with stand) 7.85 kg VESA Adaptive Sync support X Weight (with stand) 7.85 kg Component video sync Separate sync Depth (without stand) 61 mm Elicker-free technology ✓ Height (without stand) 61 mm Low Blue Uipft technology ✓ Height (without stand) 51 kg Low Blue Uipft technology ✓ Height (without stand) 51 kg World Mithred Very Bull (without stand) 51 kg Multimed of Speakers 2 Package depth 50 mm Multimed of Speakers 2 Package depth 250 mm Multimed is peaker(s)* ✓ Package eight 462 mm Weight (without stand) 450 mm 462 mm Weight (without stand) 51 kg 400 mm Weight (without stand) 51 kg Weight (without stand) 51 kg 51 kg Weight (without stand				
NVIDIA G-SYNC	Performance		-	614 mm
AMD FreeSync* X Height (with stand) 558 mm VESA Adaptive Sync support Y Width (without stand) 614 mm Component video sync Separate sync Depth (without stand) 61 mm Flicker-free technology Y Height (without stand) 3172 mm Low Buc Light technology Y Packagin data 372 mm Number of speakers 2 Package depth 50 mm Number of speakers 2 W Package depth 250 mm Bullish speaker(s)* 4 Package weight 462 mm Megapiker (lapprox.) 2 MP Package weight 10.3 kg Bullish in microphone Y Package weight 10.3 kg Bullish in microphone Y Packaging content Y Design Home Cables included HDMI, DisplayPort, USB Type-C, AC Market positioning* Home Cables included HDMI, DisplayPort, USB Type-C, AC Porduct colour Black Sustainability Y Ports & interfaces Black Sustainability certificates ENERG		•	Depth (with stand)	263 mm
VESA Adaptive Sync support Veginate without stand) 6.18 kg Component Video sync Separate sync Depth (without stand) 6.1 mm Elicker-free technology V Height (without stand) 3.7 zm Low Blue Light technology V Weight (without stand) 5.1 kg Multimedia V Package deth 5.1 kg Number of speakers 2 Package depth 250 mm Morrison 2 W Package depth 250 mm Bull-tin microphone 2 W Package weight 10.3 kg Bull-tin microphone 2 W Package weight 10.3 kg Bull-tin microphone 2 W Package type 80x Bull-tin microphone 2 Mm Cables included HDMI, DisplayPort, USB Type-C AC Bull-tin microphone Black Sustainability Mm Mm <td></td> <td></td> <td>Height (with stand)</td> <td>558 mm</td>			Height (with stand)	558 mm
Component video sync Separate sync Depth (without stand) 6.1 mm Flicker, free technology v Height (without stand) 372 mm Low Blue Light technology v Weight (without stand) 372 mm Without Stand) 372 mm Without Stand) 372 mm Without Stand) 5.1 kg Multimedia V Package depth Weight (without stand) 690 mm RAMS rated power 2 W Package width 690 mm Megapixel (approx.) 2 MP Package height 462 mm Megapixel (approx.) 2 MP Package height 10.3 kg Multim indrophone V Package height 10.3 kg Multim indrophone V Package weight 10.3 kg With indrophone V Package theight 10.3 kg With ind	•		Weight (with stand)	7.85 kg
Flicker-free technology			Width (without stand)	614 mm
Low Blue Light technology Y Weight (without stand) 5.1 kg Muttimedia Packaging data Number of speakers 2 Package width 690 mm RMS rated power 2 W Package depth 250 mm Built-in speaker(s)* 2 MP Package height 462 mm Built-in incomera* 2 MP Package weight 10.3 kg Built-in momphone 4 Package type Box Built-in momphone 4 Package type Box Built-in camera* 4 Mome Cables included 4 Mm Market positioning* Home Cables included 4 Mm DispayPort, USB Type-C, AC Product colour Black Manual 4 Mm SmartControl Feet colour Black Manual 5 Mm SmartControl Ports & interfaces Black Sustainability SmartControl Built-in USB Nub* 7 Doesn't contain PVC/BFR, Mercury USB pub version 3,2 Cept (3.1 Gen 1) Other features USB pub version 1 <th< td=""><td></td><td>Separate sync</td><td>Depth (without stand)</td><td>61 mm</td></th<>		Separate sync	Depth (without stand)	61 mm
Multimedia Packaging data Number of speakers 2 Package width 690 mm RMS rated power 2 W Package depth 250 mm Built-in speaker(s) - Package height 462 mm Megapixel (approx.) 2 MP Package weight 10.3 kg Built-in camera - Packaging content Design - Stand included -/ Market positioning Home Cables included HDMI, DisplayPort, USB Type-C, AC Product colour Black Manual -/ Feet colour Black Sustainability Ports & interfaces Black Sustainability Ports & interfaces - Sustainability certificates ENERGY STAR, TCO USB hub version 3.2 Gen 1 (3.1 Gen 1) Other features ENERGY STAR, TCO USB upstream port type USB Poyer C USB Power Delivery revision 3.0 USB rybre-C USB Power Delivery (USB PO)	Flicker-free technology	✓	Height (without stand)	372 mm
Number of speakers 2 Package depth 250 mm RNS rated power 2 W Package depth 250 mm Built-in speaker(s)* 7 Package helpht 250 mm Megapixel (approx.) 2 MP Package weight 10.3 kg Built-in camera* 7 Package weight 10.3 kg Built-in camera* 4 Package weight 10.3 kg Built-in camera* 4 Package type Box Stand included 4 Cables included HDMI, DisplayPort, USB Type-C, AC Product colour Black Manual 7 Front bezel colour Black Sustainability Built-in colour Black Sust	Low Blue Light technology	✓	Weight (without stand)	5.1 kg
RMS rated power 2 W Package depth 250 mm Built-in pspaker(s)** 2 MP Package weight 462 mm Built-in microphone 2 MP Package weight 10.3 kg Built-in microphone 2 MP Package type Box Built-in camera* 2 V Package type Box Built-in camera* 2 V Package type Box Market positioning* Home Packaging content V Market positioning* Home Cables included MDMI, DisplayPort, USB Type-C, AC Market positioning* Home Amnual V Front bezel colour Black Bundled Software SmartControl Front bezel colour Black Sustainability SmartControl Feet colour Black Sustainability SmartControl Ports & Interface Black Sustainability SmartControl USB puber between port spe USB puber between port spe Sustainability Sustainability USB puber colluptration port spe 2 Sus Type-C USB Power Delivery up to	Multimedia		Packaging data	
Built-in speaker(s)* Y Package height 462 mm Megapixel (approx.) 2 MP Package weight 10.3 kg Built-in microphone Y Package type box Built-in camera* Y Packaging content Design Stand included HDM, DisplayPort, USB Type-C, AC Package proper to Colour* Market positioning* Black Manual * Front bezel colour Black Burdled software SmartControl Feet colour Black Sustainability SmartControl Ports & interfaces Y Sustainability certificates ENERGY STAR, TCO Built-in USB hub* Y USB proper contain **Nergy STAR, TCO Built-in USB hub* Y USB Power Contain **Des Regy STAR, TCO USB power Spelivery (specificates) USB Type-C USB Power Delivery revision 3.0 Act Ture USB power Delivery (usb pot Alternate Mode Y Exture chanacement Smarttmage Act Ture chanacement Smarttmage USB Power Delivery (usb pot pot Alternate Mode Y Exture chanacement	Number of speakers	2	Package width	690 mm
Megapixel (approx.) 2 MP Package weight 10.3 kg Built-in microphone V Package type Box Built-in camera* V Packaging content Design Stand included V Market positioning * Home Cables included HDMI, DisplayPort, USB Type-C, AC Product colour* Portact colour * Black Manual V Feet colour Black Sustainability V Ports & interfaces Sustainability certificates ENERGY STAR, TCO Built-in USB hub * V Doesn't contain PVC/BFR, Mercury USB bu version 3.2 Gen 1 (3.1 Gen 1) Other features V USB upstream port type USB Type-C USB Power Delivery evision 3.0 USB type-C DisplayPort Alternate V Exercif rhish type Textured USB Power Delivery (USB PD) V Exercif principle packaging material 100 (Bit Type-C) (B	RMS rated power	2 W		250 mm
Built-in microphone	Built-in speaker(s) *	✓		
Built-in camera*	Megapixel (approx.)	2 MP		•
Design Stand included ✓ Market positioning ** Home Cables included HDMI, DisplayPort, USB Type-C, AC Product colour ** Black Manual ✓ Front bezel colour Black Bundled software SmartControl Feet colour Black Sustainability Ports & interfaces Sustainability certificates ENERGY STAR, TCO Built-in USB hub ** ✓ Doesn't contain PVC/BFR, Mercury USB upstream port type USB Type-C USB Power Delivery evision 3.0 USB upstream port type 1 Exterior finish type Textured USB Power Delivery (USB PDI) ✓ Picture enhancement Smart/mage USB Power Delivery (USB PDI) ✓ Regulatory Approvals EAEU RoHS; FCC Class B; ICES-003; CE Mark HDMI ** ✓ Heavy metals free Picture enhancement Smart/mage HDMI yersion 1 Low Blue mode ✓ Ferror or CE Mark	Built-in microphone	✓	Package type	Box
Market positioning * Home Black Manual	Built-in camera *	✓	Packaging content	
Front bezel colour* Black Black Bundled software SmartControl Front bezel colour Black Sustainability Ports & Interfaces Built-in USB hub* V/BFR, Mercury USB hub version 3.2 Gen 1 (3.1 Gen 1) USB hub version USB Type-C USB Type-C USB Power Delivery revision 3.0 Number of upstream port type USB Type-C USB Power Delivery revision 3.0 Number of upstream port sype USB Type-C USB Power Delivery revision 3.0 Number of upstream port Alternate V/BFR Mercury USB Power Delivery (USB PD) V/BFR Mercury WSB Mover Delivery (USB PD) V/BFR Me	Design		Stand included	✓
Product colour Black Manual Year Front bzel colour Black Budled software SmartControl Feet colour Black Budled software SmartControl Ports & interfaces Sustainability certificates ENERGY STAR, TCO USB hub version 3.2 Gen 1 (3.1 Gen 1) Other features \$1.0 USB upstream port type USB Type-C USB Power Delivery evision 3.0 Number of upstream ports 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode Ye Recyclable packaging material 100% USB Power Delivery (USB PD) Ye Regulatory Approvals EAEU RoHS; FCC Class B; ICES-003; CEM ark HDMI ports quantity 1 Heavy metals free Hg (mercury) HDMI ports quantity 1 LowBlue mode Ye HDMI ports quantity 1 LowBlue mode Ye HDDP Ye Compliance certificates ROHS HDCP Ye Mean time between failures (MTBF) 70000 h HDCP Ye Certification CB, TUV/GS, TUV Ergo, SEMKO, CU-LEAC; Class B, ICES-003, CE Mark HDCP Ye Certification CB, TUV/GS, TUV Ergo, SEMKO, CU-LEAC; CLEAC, CA, EAEU RoHS, FCC Class B, ICES-003, CE Mark Fergono	Market positioning *	Home	Cables included	HDMI, DisplayPort, USB Type-C, AC
Feet colour Black Sustainability Ports & interfaces Built-in USB hub *			Manual	✓
Ports & interfaces Sustainability certificates ENERGY STAR, TCO Built-in USB hub* / Doesn't contain PVC/BFR, Mercury USB hub version 3.2 Gen 1 (3.1 Gen 1) Other features USB upstream port type USB Type-C USB Power Delivery revision 3.0 Number of upstream ports 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode Picture enhancement SmartImage Mode Recyclable packaging material 100% USB Power Delivery (USB PD) FAEU RoHS; FCC Class B; ICES-003; CE Mark USB Power Delivery up to 65 W Regulatory Approvals EAEU RoHS; FCC Class B; ICES-003; CE Mark HDMI ports quantity 1 Heavy metals free Hg (mercury) HDMI ports quantity 1 LowBlue mode ✓ DisplayPort version 1.2 Energy efficiency class (old) F Audio output ✓ Compliance certificates ROHS HDCP version 1.4 Certification CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, FCC Class B, ICES-003, CE Mark VESA mounting* <t< td=""><td>Front bezel colour</td><td>Black</td><td>Bundled software</td><td>SmartControl</td></t<>	Front bezel colour	Black	Bundled software	SmartControl
Built-in USB hub* Very Bern, Mercury USB hub version See 1 (3.1 Gen 1) USB Type-C USB Power Delivery revision Sexterior finish type Exterior finish type	Feet colour	Black	Sustainability	
USB hub version 3.2 Gen 1 (3.1 Gen 1) USB lub version 3.2 Gen 1 (3.1 Gen 1) USB lub version 3.0 Number of upstream port type USB Type-C USB Power Delivery revision 3.0 Number of upstream ports 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) V USB Power Delivery up to 65 W Regulatory Approvals EAEU RoHS; FCC Class B; ICES-003; CE Mark HDMI * **HDMI ports quantity 1 Heavy metals free Heavy metals free Hg (mercury) HDMI version 1.4 LowBlue mode V DisplayPorts quantity 1 LowBlue mode V DisplayPort version 1.2 Energy efficiency class (old) F Audio output V HDCP version 1.4 HEAVY Mean time between failures (MTBF) HDCP version 1.4 **HDCP version 1.4 **HDCP version 1.4 **Ergnommics **VESA mounting ** VESA mounting interface 100 x 100 mm Post-consumer recycled plastic 25% Cable lock slot ** **VESA mounting interface 100 x 100 mm Post-consumer recycled plastic 25% Cable lock slot type Kensington Height adjustment ** **VESA mounting interface 15 cm	Ports & interfaces		Sustainability certificates	ENERGY STAR, TCO
USB upstream port type USB Type-C USB Power Delivery revision 3.0 Number of upstream ports 1 Exterior finish type Textured USB Type-C DisplayPort Alternate Mode Picture enhancement SmartImage USB Power Delivery (USB PD) V Regulatory Approvals CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; CE Mark HDMI * V Heavy metals free Hg (mercury) HDMI ports quantity 1 EasyRead mode V HDMI version 1.4 LowBlue mode V DisplayPort squantity 1 LowBlue mode V DisplayPort version 1.2 Energy efficiency class (old) F HDCP V Mean time between failures (MTBF) 70000 h HDCP version 1.4 Compliance certificates ROHS HDCP version 1.4 Cetification CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, FCC Class B, ICES-003, CE Mark Fronomics VESA mounting * Y Recycling data VESA mounting interface 100 x 100 mm Post-consumer recycled plastic 85% Cable lock slot type Kensington Harmonized System (HS) code 85285210 Height adjustment * Y Harmonized System (HS) code 14	Built-in USB hub *	✓	Doesn't contain	PVC/BFR, Mercury
Number of upstream ports USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to 65 W Heavy metals free Heavy metals free Heavy metals free Home DisplayPorts quantity HDMI version Liz DisplayPort version Audio output HDCP HDCP HDCP HDCP HDCP HDCP HDCR HDCR HDCR HDCR HDCR HDCR HDCR HDCR	USB hub version	3.2 Gen 1 (3.1 Gen 1)	Other features	
USB Type-C DisplayPort Alternate Mode Wode Wode USB Power Delivery (USB PD) V Service Delivery up to MDMI* HDMI version I.4 LowBlue mode LowBlue mode LowBlue mode Wean time between failures (MTBF) HDCP version I.4 HDCP version I.4 HDCP version I.4 HDCP version I.4 Certification Tergonomics VESA mounting * VESA mounting interface Low Slot type Renight adjustment * V Kensington Kensing	USB upstream port type	USB Type-C	USB Power Delivery revision	3.0
Mode Weekling packaging material Weekling packaging packaging packaging packaget packa	Number of upstream ports	1	Exterior finish type	Textured
Mode USB Power Delivery (USB PD) V Sepower Delivery up to Sepower Delivery (USB PD) Sepower Delivery (USB PD) Sepower Delivery (USB PD) Sepower Delivery up to Sepower Delivery up to Sepower Delivery (USB PD) Sepower Delivery up to Sepower Delivery (USB PD) Sepower Delivery (USB POH) Sepower Pewer Pohy (USB POH) Sepower Delivery (USB POH) Sepower Pewer Pew		/	Picture enhancement	SmartImage
USB Power Delivery up to 65 W Regulatory Approvals EAEU RoHS; FCC Class B; ICES-003; CE Mark HDMI ports quantity 1 1 Heavy metals free Hg (mercury) HDMI version 1.4 LowBlue mode ✓ DisplayPorts quantity 1 1 LowBlue mode ✓ DisplayPort version 1.2 Energy efficiency class (old) F Audio output ✓ HDCP		-	Recyclable packaging material	100%
HDMI ports quantity HDMI version 1.4 LowBlue mode LowBlue mode V DisplayPorts quantity 1.2 Audio output HDCP HDCP version 1.4 Certification VESA mounting* VESA mounting * Panel mounting interface 100 x 100 mm Cable lock slot * Cable lock slot type Height adjustment 1.5 Certification Heavy metals free Hg (mercury) Hg (mercur) Hg (mercur) Hg (mercur) Hg (metals Hg (metals Hg (as)) Hg (metals Hg (as) Hg (as) Hg (metur) Hg (as) Hg			Regulatory Approvals	
HDMI version 1.4 EasyRead mode LowBlue mode Low	HDMI *	✓		
DisplayPorts quantity DisplayPort version 1.2 Audio output Audio output HDCP HDCP HDCP version I.4 **Certification **Certificates	HDMI ports quantity	1	-	-
DisplayPort version 1.2 Energy efficiency class (old) F Audio output	HDMI version	1.4	•	
Audio output HDCP HDCP version 1.4 Kersington Compliance certificates Mean time between failures (MTBF) Certification	DisplayPorts quantity	1		
HDCP version 1.4 Certification Certification CER, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, FCC Class B, ICES-003, CE Mark VESA mounting *	DisplayPort version	1.2		
HDCP version 1.4 Ergonomics VESA mounting * Panel mounting interface CB, TUV/GS, TUV Ergo, SEMKO, CUEAC, EAEU ROHS, FCC Class B, ICES-003, CE Mark Recycling data Post-consumer recycled plastic Cable lock slot * Cable lock slot type Kensington Height adjustment * Height adjustment VESA mounting interface Accepting data Recycling data Post-consumer recycled plastic Accepting data Harmonized System (HS) code Accepting data Harmonized System (HS) code Accepting data Harmonized System (HS) code Accepting data 15 cm	Audio output	✓		
Ergonomics VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment 1.4 Certification Certification EAC, EAEU ROHS, FCC Class B, ICES-003, CE Mark Recycling data Post-consumer recycled plastic 85% Logistics data Harmonized System (HS) code 85285210 Height adjustment * Height adjustment 15 cm	HDCP	✓	Mean time between failures (MTBF)	
VESA mounting *	HDCP version	1.4	Certification	
Panel mounting interface 100 x 100 mm Post-consumer recycled plastic 85% Cable lock slot * Logistics data Cable lock slot type Kensington Harmonized System (HS) code 85285210 Height adjustment * John Height adjustment 15 cm	Ergonomics			ICES-003, CE Mark
Cable lock slot *	VESA mounting *	✓	Recycling data	
Cable lock slot type Kensington Harmonized System (HS) code 85285210 Height adjustment 15 cm	Panel mounting interface	100 x 100 mm	Post-consumer recycled plastic	85%
Cable lock slot type Kensington Harmonized System (HS) code 85285210 Height adjustment * ✓ Height adjustment 15 cm	Cable lock slot *	✓	Logistics data	
Height adjustment * Height adjustment 15 cm	Cable lock slot type	Kensington		85285210
	Height adjustment *	✓	-,,	
Pivot 🗸	Height adjustment	15 cm		
	Pivot	✓		



8712581776145

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.