



Cooler Master's high-performance SickleFlow series is back and better than ever in the all-new SickleFlow Edge 120 ARGB 3-Pack Fan Kit. With highlight features such as an enhanced fan blade, a newly redesigned frame, an updated loop dynamic bearing system, and the A1 Mini LED controller, the SickleFlow Edge 3-Pack provides maximal performance and triple the power.

## SICKLEFLOW EDGE 120 ARGB 3-PACK FAN KIT




**Enhanced fan blade**

An improved fan blade provides higher fan speed, air pressure, and airflow while sticking to the same low noise level the SickleFlow is known for.



**Redesigned frame**

The SickleFlow's signature lines are now included in the frame design to provide a more cohesive product design.



**Improved bearing system**

An enhanced loop dynamic bearing system keeps things running silently smooth.



**A1 Mini LED controller**

Control and customize your SickleFlow Edge 120 Fan Kit's lighting with a compact, easy-to-use mini controller.

**Enhanced fan blade** - An improved fan blade provides higher fan speed, air pressure, and airflow while sticking to the same low noise level the SickleFlow is known for.

**Redesigned frame** - The SickleFlow's signature lines are now included in the frame design to provide a more cohesive product design.

**Improved bearing system** - An enhanced loop dynamic bearing system keeps things running silently smooth.

**A1 Mini LED controller** - Control and customize your SickleFlow Edge 120 Fan Kit's lighting with a compact, easy-to-use mini controller.

## SPECIFICATIONS

Product Name	SickleFlow Edge 120 ARGB 3-Pack Fan Kit	
Product Number	MFX-B2DN-253P2-R2	
Exterior Color	Black	
Fan	Dimensions (L x W x H)	120 x 120 x 25 mm (4.7 x 4.7 x 1 in)
	Profiles	Addressable Gen 2 RGB
	Speed (RPM)	690~2500 $\pm$ 10% RPM
	Airflow (CFM)	120m <sup>3</sup> /h (70.7CFM)
	Noise Level dB(A)	27.2 dB(A)
	Bearing	Loop dynamic bearing
	Pressure (mmH <sub>2</sub> O)	3.61 mmH <sub>2</sub> O
	MTTF	>160,000 hours
	Power Connector	4-Pin (PWM)
	Rated Voltage (VDC)	12 VDC
	Rated Current (A)	0.2 A
	Safety Current	0.3 A
	Power Consumption	2.4 W
	RGB Connector	3-Pin ARGB
	RGB Rated Voltage	5 VDC
	RGB Rated Current	0.21 A
	Weight	168 g (0.37 lbs)
Warranty	2 years	

## PACKING INFORMATION

EAN code	4719512146064
UPC code	884102118388
Net weight	0.551 kg
Package dimension (L x W X H)	14 x 9 x 15.5 cm
Carton dimension (L x W x H)	44 x 28.5 x 35 cm
Units/CTN	18

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	7200	40	N/A
40'	15120	40	N/A
40 HQ	18144	48	N/A