Brother RJ3250WBL label printer Direct thermal 203 x 203 DPI 127 mm/sec Wireless Ethernet LAN Wi-Fi Bluetooth

Brand : Brother

Product name : RJ3250WBL

Product code: RJ-3250WBL

Rugged Mobile Label Printer, Bluetooth 5.0, Wi-Fi, IP54, 203dpi, 807g

Brother RJ3250WBL label printer Direct thermal 203 x 203 DPI 127 mm/sec Wireless Ethernet LAN Wi-Fi Bluetooth:

The RJ-3250WBL mobile printer offers a fast print solution, designed to endure relentless usage.

With Bluetooth and WiFi connectivity, this compact and portable printer is ready to support busy workforces' labelling and receipt requirements.

Whether you wear on-body or mount on a surface, this 3-inch mobile printer is ready to connect and print, wherever needed.
Brother RJ3250WBL. Print technology: Direct thermal, Maximum resolution: 203 x 203 DPI, Print speed: 127 mm/sec. Connectivity technology: Wireless. Battery type: Built-in battery, Battery technology: Lithium Polymer (LiPo). Product colour: Black

Printing

Print technology *	Direct thermal
Maximum resolution *	203 x 203 DPI
Print speed *	127 mm/sec
Maximum printing width *	7.2 cm
Minimum print length	3 m

Paper handling

Maximum label width	7.6 cm
Maximum roll diameter	6.6 cm
Media thickness	0.058 - 0.090 mm

Ports & interfaces

Connectivity technology *	Wireless
Ethernet LAN *	✔
Wi-Fi *	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth	✔
Bluetooth version	5.0
USB port *	✔

Performance

Page description languages	CPCL-native, ESC P, Raster_P
Internal memory	256 MB
Flash memory	128 MB
Built-in barcodes	AZTECCODE, CODABAR (NW-7), Code 128 (A/B/C), Code 93, Data Matrix, EAN13, EAN8, GS1 DataBar Limited, GS1-128, ITF-25, MSI, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E

Design

Product colour *	Black

Power

Battery type	Built-in battery
Battery technology	Lithium Polymer (LiPo)
Battery capacity	3000 mAh

System requirements

Windows operating systems supported	✔
Mobile operating systems supported	Android, iOS

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	-20 - 55 °C

Weight & dimensions

Width	117 mm
Depth	180 mm
Height	77 mm
Weight	807 g

Logistics data

Harmonized System (HS) code	84433210

00125026641 09

012502664109

4977766814843