

TP-Link Omada S7500-48XF4C network switch Managed

Brand : TP-Link Product family: Omada Product code: S7500-48XF4C

Product name: S7500-48XF4C

- 48× 10 Gbps SFP+ slots and 4× 100 Gbps QSFP28 slots
- Physical stacking for built-in redundancy and performance
- L3 Features: OSPF, BGP, IS-IS, VRRP, PIM-SM/PIM-DM/PIM-SSM, ECMP, PBR
- Security Strategies: Secure Boot, RADSEC, IMPB, SFTP, 802.1X, Port Security
- Highly available with two field-replaceable power supplies,* VRRP, ERPS, BFD
- Easy O&M: NETCONF, Configuration Rollback, Hot Patching, and RSPAN
- Centralized cloud management via the web or the Omada app

S7500-48XF4C - Omada Pro 48-Port 10G Stackable L3 Managed Aggregation Switch with $4 \times 100G$ Slots TP-Link Omada S7500-48XF4C. Switch type: Managed. USB 2.0 ports quantity: 3, Console port: RJ-45. MAC address table: 128000 entries, Switching capacity: 1760 Gbit/s. Rack mounting





Management features		Protocols	
Switch type *	Managed	Management protocols	SNMPv1/v2c/v3
	Manageu		SIMMFV1/V2C/V3
Web-based management	•	Design	
Cloud-managed	✓	Rack mounting *	✓
Ports & interfaces		Stackable *	✓
Basic switching RJ-45 Ethernet ports type *	×	Power	
SFP+ module slots quantity	48	Power source *	AC
Console port	RJ-45	Power supply included *	✓
QSFP28 ports quantity	4	AC input voltage	110 V
USB 2.0 ports quantity	3	AC input frequency	60 Hz
Network		Power consumption (max)	86.7 W
10G support *	1	Power over Ethernet (PoE)	
Flow control support	✓	Power over Ethernet (PoE) *	×
Link aggregation	✓	Operational conditions	
Rate limiting	✓	Operating temperature (T-T)	-5 - 40 °C
Spanning tree protocol	✓	Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN data rates	1000,10000,40000,100000 Mbit/s	Operating relative humidity (H-H)	10 - 90%
VLAN support	✓	Storage relative humidity (H-H)	5 - 90%
Data transmission		Heat dissipation	295.85 BTU/h
Switching capacity *	1760 Gbit/s	Weight & dimensions	
Forwarding rate	610.1 Mpps	Width	440 mm
MAC address table *	128000 entries	Depth	380 mm
Jumbo frames support	✓	Height	44 mm
Jumbo frames	9000	Packaging content	
Packet buffer memory	8 MB	Cables included	AC, LAN (RI-45)
• •			

Security		Packaging data	
DHCP features	DHCP client	Package type	Box
Multicast features			
Multicast support	✓		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.