

APC Easy UPS On-Line, 3kVA, Lithium-ion, Rack/Tower 4U, 230V, 6 IEC C13 + 1 IEC C19 outlets, Intelligent Card Slot, Extended runtime, W/ rail kit

Brand : APC

Product code: SRVL3KRILRK

Product name : Easy UPS On-Line, 3kVA, Lithium-ion, Rack/Tower 4U, 230V, 6 IEC C13 + 1 IEC C19 outlets, Intelligent Card Slot, Extended runtime, W/ rail kit

Easy UPS On-Line, 3kVA, Lithium-ion, Rack/Tower 4U, 230V, 6 IEC C13 + 1 IEC C19 outlets, Intelligent Card Slot, Extended runtime, W/ rail kit

APC Easy UPS On-Line, 3kVA, Lithium-ion, Rack/Tower 4U, 230V, 6 IEC C13 + 1 IEC C19 outlets, Intelligent Card Slot, Extended runtime, W/ rail kit. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 7 AC outlet(s). Battery technology: Lithium-Ion (Li-Ion), Battery voltage: 48 V, Typical backup time at full load: 45 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 4U. Width: 438 mm, Depth: 616 mm, Height: 172 mm





| Features | | Battery | |
|---|--|---|--|
| FeaturesUPS topology *Double-conversion (Online)Output power capacity *3 kVAOutput power *2700 WWaveform *SineInput operation voltage (min) *110 VInput operation voltage (max) *300 VInput frequency *40/70 HzOutput frequency *50/60 HzSurge energy rating945 JEfficiency90%Crest factor3:1 | Battery Typical backup time at half load Battery life (max) Battery recharge time Design Form factor * Rack capacity Cooling type Built-in fan Product colour * Control type Display type International Protection (IP) code | 88 min 10 year(s) 4.8 h Rackmount/Tower 4U Active ✓ Black Buttons LCD IP20 | |
| ECO mode Emergency Power Off (EPO) Noise level Audible alarm(s) Audible alarm modes Power source type Detachable power cord | ✓ ✓ 50 dB ✓ Low battery alarm, Overload alarm AC ✓ | Certification Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Non-operating altitude | CB , CE, EAC, IEC 62619, KC, RCM, TISI, UKCA, UN 38.3, RoHS -20 - 50 °C 0 - 95% 0 - 95% 0 - 15000 m |
| Ports & interfaces | | Technical details | 0 - 19000 m |
| AC outlet types Power plug AC outlets quantity USB port RS-232 ports Modem (RJ-11) ports Ethernet LAN (RJ-45) ports | C13 coupler, C19 coupler C20 coupler 7 AC outlet(s) ✓ 1 1 1 | Compliance certificates Weight & dimensions Width Depth Height Weight Package width | CE, RoHS, UKCA 438 mm 616 mm 172 mm 38.3 kg 800 mm |

Battery

Battery technology Battery voltage Typical backup time at full load Lithium-Ion (Li-Ion) 48 V 45 min


Weight & dimensionsPackage depth600 mmPackage height480 mmPackage weight50.6 kgPackaging dataRack mount kit✓Cables includedPhone (RJ-11), Power load cable, RJ-45, RS-232, USB cableManual✓





731304436805

0731304436805



8592978530730

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.