## **PHILIPS**

## Philips Signage Solutions 49BDL2105X/00 Signage Display 123.2 cm (48.5") IPS 500 cd/m $^2$ Full HD Black 24/7

Solutions

Product name: 49BDL2105X/00

49BDL2103X/00

Philips Signage Solutions 49BDL2105X/00. Display diagonal: 123.2 cm (48.5"), Display technology: IPS, Display resolution:  $1920 \times 1080$  pixels, Display brightness:  $500 \text{ cd/m}^2$ , HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black

Display		Audio	
Display resolution * Display brightness * HD type * Native aspect ratio Response time Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Display number of colours	Direct-LED  123.2 cm (48.5")  IPS  1920 x 1080 pixels  500 cd/m²  Full HD  16:9  8 ms  1100:1  500000:1  178°  178°  1.07 billion colours  0.55926 x 0.55926 mm  123 cm  3%	Built-in speaker(s) * Number of built-in speakers RMS rated power	2 20 W
		<b>Design</b> Placement supported *	Indoor
		Orientation Product colour * VESA mounting * Panel mounting interface Mounting type	Horizontal/Vertical Black  ✓ 400 x 400 mm Wall
		Performance	
		On Screen Display (OSD) languages Operating hours (hours/days)	Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Russian, Turkish 24/7
Ports & interfaces		Mean time between failures (MTBF)	·
HDMI ports quantity * HDMI version HDMI input ports quantity DVI port *	2 2.0 2	Power	
		Power consumption (typical) * Power consumption (standby) *	100 W 0.5 W
DVI-D ports quantity	1	Weight & dimensions	
VGA (D-Sub) input ports 1 DisplayPorts quantity * 2 DisplayPorts in 1 DisplayPorts out 1	2 1	Display width Display depth Display height Display weight	1077.6 mm 93.1 mm 607.8 mm 21.7 kg
USB port *	/	Packaging content	
USB ports quantity 1 USB version 2.0 USB connector type USB Type-A Ethernet LAN * ✓	Remote control included Batteries included Cables included	DisplayPort, AC, IR sensor, LAN	
Ethernet LAN (RJ-45) ports	2	0	(RJ-45)
Audio (L/R) in	1	Operational conditions	0. 40.00
Audio (L/R) out Remote (IR) input Remote (IR) output OPS module slot	1 1 1	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 20 - 80% -20 - 60 °C 5 - 95%
		Certificates	
		Certification	CE FCC Class A Restriction of Hazardous Substances (ROHS) CB ETL BSMI





685417589180

0685417589180



8712581785918

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.