



APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19

Brand : APC

Product code: AP8659EU3

Product name : Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19
APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19. PDU types: Metered, Metered-by-outlet, Switched, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 3 m, Certification: EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, PSE, UL, VCCI Class A, VDE. Monitoring: Current, Power, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on. Nominal input voltage: 200-230 V, AC input frequency: 50 - 60 Hz, Nominal output voltage: 230 V



Design		Power	
PDU types *	Metered, Metered-by-outlet, Switched	Maximum input current per phase	16 A
Rack capacity *	0U	Maximum total current draw per phase	16 A
Mounting	Vertical	Maximum power	3680 W
Product colour	Black	Weight & dimensions	
Ports & interfaces		Dimensions (WxDxH)	56 x 51 x 1829 mm
AC outlets quantity *	24 AC outlet(s)	Weight	6.77 kg
Power plug	IEC309	Packaging data	
AC outlet types *	C13 coupler, C19 coupler	Package dimensions (WxDxH)	162 x 117 x 2038 mm
Features		Package weight	9.05 kg
Cable length	3 m	Operational conditions	
Certification	EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, PSE, UL, VCCI Class A, VDE	Operating temperature (T-T)	-5 - 45 °C
		Storage temperature (T-T)	-25 - 65 °C
Management features		Operating relative humidity (H-H)	5 - 95%
Monitoring	Current, Power, Voltage	Storage relative humidity (H-H)	5 - 95%
Outlet control	Lock-out, Recycle, Turn off, Turn on	Operating altitude	0 - 3000 m
Power		Non-operating altitude	0 - 15000 m
Nominal input voltage *	200-230 V	Technical details	
AC input frequency	50 - 60 Hz	Compliance certificates	RoHS
Nominal output voltage	230 V		
Load capacity	3680 VA		



0731304299516



731304299516

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.