

TP-Link 300Mbps Wireless N Travel WiFi Router

Brand: TP-Link Product code: TL-WR802N V4

Product name: 300Mbps Wireless N Travel WiFi Router


300Mbps Wireless N Nano Router, 2.4-2.4835 GHz, 1x Fast Ethernet, USB, White/Blue TP-Link 300Mbps Wireless N Travel WiFi Router. WAN connection type: RJ-45. Wi-Fi band: Single-band (2.4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Security algorithms: 128-bit WEP, 152-bit WEP, 64-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Product type: Tabletop router, Product colour: Blue, White





WAN connection		Design	
Ethernet WAN *	✓	Product colour	Blue, White
DSL WAN *	×	LED indicators	✓
SIM card slot *	×	On/off switch	✓
3G/4G USB modem compatibility *	×	Product type *	Tabletop router
WAN connection type	RJ-45	Certificates	
Wireless LAN features		Certification	CE, FCC, RoHS
Wi-Fi band *	Single-band (2.4 GHz)	Packaging content	
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	Manual	✓
WLAN data transfer rate (max) * Wi-Fi standards	300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Quick installation guide	✓
Network	002.11b, 002.11g, WI-114 (002.11ii)	Antenna	
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates	Fast Ethernet 10,100 Mbit/s	Antenna design *	Internal 270M: -65dBm@10% PER , 130M: -70dBm@10% PER , 108M: -82dBm@10% PER , 54M: -73dBm@10% PER , 11M: -82dBm@8% PER , 6M: -86dBm@10% PER , 1M: -90dBm@8% PER
Cabling technology Networking standards	10/100Base-T(X) IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Receive power	
Port triggering	✓	Transmit power	CE: , <20dBm(2.4GHz) , FCC: , <30dBm
Dynamic DNS (DDNS)	✓		Coupili
VPN Passthrough	✓	Power	
VPN support	PPTP, L2TP, IPSec	Power source type *	DC 5 V
Mobile network		Output voltage Output current	1 A
3G	×		10
4G	×	Operational conditions	
Ports & interfaces		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Ethernet LAN (RJ-45) ports *	1	Operating relative humidity (H-H)	10 - 90%
USB port *	✓	Storage relative humidity (H-H)	5 - 90%
Memory card slot(s)	x		
DC-in jack	✓		


Management for the second		Contain manufacture of	
Management features		System requirements	
Web-based management Reset button	1	Windows operating systems supported	Windows 2000, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista Business,
Security			
Security algorithms	128-bit WEP, 152-bit WEP, 64-bit WEP, WPA, WPA-PSK, WPA2, WPA2- PSK		
Firewall Stateful Packet Inspection (SPI)	✓ ✓		
DoS attack prevention	✓		
Filtering	✓		
MAC address filtering	✓		
IP address filtering	✓		
DMZ support	✓		
Protocols			Windows Vista Business x64, Windows Vista Enterprise, Windows
DHCP client DHCP server Universal Plug and Play (UPnP)	✓ ✓		Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
		Linux operating systems supported	✓
		Mac operating systems supported	macOS
		Weight & dimensions	
		Width	57 mm
		Depth	57 mm
		Height	18 mm
		Packaging data	
		Package width Package depth	110 mm 109 mm
		Package height	73.5 mm
		Package weight	240 g
		Other features	
		Mobile network connection	x
		WLAN data transfer rates supported	11,54,300 Mbit/s
		Frequency range	2.4 - 2.4835 GHz
		USB ports quantity	1 ID Static ID DDDGE DDTD 12TD
		Supported WAN type Frequency band	IP, Static IP, PPPoE, PPTP, L2TP 2.4 GHz
		Rack mounting	X
		xDSL connection	×











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.