## Samsung MUF-256BE USB flash drive 256 GB USB Type-A 3.2 Gen 1 (3.1 Gen 1) Silver

**Brand :** Samsung **Product code:** MUF-256BE3/APC

Product name: MUF-256BE

- Transfer files with speeds up to 400MB/s. Performance varies by capacity.
- Reliable and secure storage for your photos, videos, music, and files.
- Durable metal casing with integrated key ring to prevent loss.
- USB 3.2 Gen 1 (Type A) flash drive with backwards compatibility (USB 2.0).
- Protection from water, extreme temperatures, shock, magnets and x-rays.  $\mbox{\sc MUF-}256\mbox{\sc BE3/APC}$

Samsung MUF-256BE. Capacity: 256 GB, Device interface: USB Type-A, USB version: 3.2 Gen 1 (3.1 Gen

1), Read speed: 300 MB/s, Write speed: 30 MB/s. Form factor: Capless. Password protection. Weight:

10.9 g. Product colour: Silver





Performance		Weight & dimensions	
	256 GB	Weight	10.9 g
	USB Type-A 3.2 Gen 1 (3.1 Gen 1) 300 MB/s 30 MB/s	Packaging data	
		Package width	102 mm
Write speed		Package depth	154 mm
Plug and Play		Package height	12 mm
Design		Package weight Package type	24 g Blister
Form factor *	Capless Silver Magnet proof, Shock resistant, Temperature proof, Waterproof, X-	Packaging content	
Product colour *		Quantity per pack	1 pc(s)
Protection features		Operational conditions	
	rai, praef		
Waterproof up to Certification	ray proof 1 m KC, FCC, CE, VCCI, RCM	Operating temperature (T-T) Storage temperature (T-T) Operating shock	-25 - 85 °C -40 - 85 °C
• •	1 m	Storage temperature (T-T) Operating shock	
Certification	1 m	Storage temperature (T-T)	-40 - 85 °C 1500 G
Certification Security	1 m KC, FCC, CE, VCCI, RCM	Storage temperature (T-T) Operating shock Operating vibration	-40 - 85 °C 1500 G 15000 G
Certification  Security  Password protection	1 m KC, FCC, CE, VCCI, RCM	Storage temperature (T-T) Operating shock Operating vibration Duration shock	-40 - 85 °C 1500 G 15000 G
Certification  Security  Password protection  Weight & dimensions	1 m KC, FCC, CE, VCCI, RCM	Storage temperature (T-T) Operating shock Operating vibration Duration shock Other features	-40 - 85 °C 1500 G 15000 G 0.5 ms



8801643229405

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.