Ricoh fi-7300NX ADF scanner 600 x 600 DPI A4 Grey, White

Brand : Ricoh

Product name : fi-7300NX

Product code: PA03768-B001

- Scan from the scanner with touch screen operation
- Various authentication methods for improved efficiency and security
- Scan from your smart device to any business platform
- 3 types of SDKs to suit any environment
- PaperStream NX Manager and Scanner Central Admin for centralized management
- Paper Protection function protects scans from jamming by detecting anomalies in document length and sound
- Manual Feed Mode for scanning folded or bound documents
ADF, Duplex, 600 dpi, 4.3" TFT, USB 3.1 Gen1, LAN, 42 W
Ricoh fi-7300NX. Maximum scan size: 216 x 5588 mm, Optical scanning resolution: 600 x 600 DPI, Output colour depth: 24 bit. Scanner type: ADF scanner, Product colour: Grey, White, Display: TFT. Sensor type: Dual CCD, Daily duty cycle (max): 4000 pages, Light source: White LED (2x). Auto document feeder (ADF) input capacity: 80 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Plain paper, Plastic Card, Auto Document Feeder (ADF) media weight: 27 - 413 g/m²

Scanning

Maximum scan size *	216 x 5588 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Output colour depth	24 bit
Output greyscale depth	8 bit
Output monochrome depth	1 bit
Duplex ADF scan speed (colour, A4)	120 ipm
Black/white scanning colour modes	Grayscale, Monochrome

Design

Scanner type *	ADF scanner
Product colour *	Grey, White
Display	TFT
Display diagonal	10.9 cm (4.3")
Touchscreen	✔
Built-in display *	✔

Performance

Sensor type *	Dual CCD
Light source	White LED (2x)
Daily duty cycle (max) *	4000 pages
Scan drivers	ScanSnap, TWAIN, WIA
Ultrasonic double sheet detection	✔

Input capacity

Auto document feeder (ADF) input capacity	80 sheets

Paper handling

Scanning media types supported	Plain paper, Plastic Card
Long-paper mode	✔
Maximum ISO A-series paper size *	A4

Power

Power consumption (PowerSave)	2.4 W
Input voltage	100 - 240 V

Weight & dimensions

Width	300 mm
Depth	202 mm
Height	170 mm
Weight	49 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	270 mm
Package depth	400 mm
Package height	305 mm
Package weight	7.2 kg

Packaging content

Cables included	AC, USB
AC adapter included	✔
ADF paper chute	✔
Drivers included	✔

Sustainability

Sustainability certificates	ENERGY STAR

System requirements

Minimum storage drive space	120000 MB
Minimum processor	3.5 GHz

Paper handling

Auto Document Feeder (ADF) media weight	27 - 413 g/m²
Maximum scan width	21.6 cm
Maximum scan length	5.59 m
Minimum scan area (ADF)	50.8 x 54 mm

Ports & interfaces

USB port *	✔
USB version	3.2 Gen 2 (3.1 Gen 2)
Socket connector type	C5
Standard interfaces	Ethernet, USB 1.1, USB 2.0, USB 3.2 Gen 1 (3.1 Gen 1), Wireless LAN

Network

Wi-Fi	✔
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Ethernet LAN	✔
Supported network protocols	IPv4(15), TCP, UDP, ICMP, DHCP, HTTP/HTTPS, DNS

Power

Power supply type *	AC
Power consumption (typical)	42 W
Power consumption (off)	0.35 W

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Server operating systems supported	Windows Server 2008, Windows Server 2008 x64, Windows Server 2012 R2 x64, Windows Server 2012 x64, Windows Server 2016 x64

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	41 - 95 °F

Other features

Compliance certificates	RoHS
Background colours	Black, White

Logistics data

Country of origin	Indonesia
Pallet gross length	121.9 cm
Pallet gross width	101.6 cm
Harmonized System (HS) code	8471607000
Paper packaging weight	2.4 kg
Metal packaging weight	0 g
Wood packaging weight	0 g
Plastic packaging weight	15 g
Products per pallet (air)	40 pc(s)
Products per pallet (sea)	60 pc(s)
Pallet height (sea)	198 cm
Pallet height (air)	137 cm
Cardboard packaging weight	1.2 kg
Foil packaging weight	15 g
Polystyrene (EPS/EPP) packaging weight	200 g
Glass packaging weight	0 g

4939761309632

Catalog Object Cloud