## NETGEAR M4300-8X8F Managed L3 10G Ethernet (100/1000/10000) 1U Black

**Brand:** NETGEAR Product code: XSM4316S-100NES

Product name: M4300-8X8F

320 Gbps, 10/100/1000/10000, 1U, L3

NETGEAR M4300-8X8F. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8, USB 2.0 ports quantity: 1, Console port: RJ-45/Mini-USB. MAC address table: 16000 entries, Switching capacity: 320 Gbit/s. Networking standards: IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az. Rack mounting, Form factor: 1U





Management features		Multicast features	
Switch type *	Managed	Number of multicast groups filtered	4000
Switch layer	L3	Design	
Quality of Service (QoS) support	<b>/</b>	Rack mounting *	✓
Web-based management	<b>✓</b>	Stackable *	<b>✓</b>
ARP inspection	<b>✓</b>	Form factor	10
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports	8	LED indicators	Activity, Power, Speed
quantity *		Safety	CSA 22.2 #950, UL 1950)/cUL IEC 950/EN 60950
type * SFP+ module slots quantity	* 103 Ethernet (100/1000/10000)	Electromagnetic compatibility	CE, FCC 15 A, VCCI A, A EN 55022, (CISPR 22) A, EN 50082-1, EN 55024
Fiber optic connector	SFP+	Performance	
Console port	RJ-45/Mini-USB	Built-in processor	<b>✓</b>
USB 2.0 ports quantity	1	Processor frequency	800 MHz
Network		Internal memory	1024 MB
Networking standards *	IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az	Flash memory Noise level	256 MB 36.9 dB
10G support *	✓	Mean time between failures (MTBF)	
Cable types supported	Cat5, Cat5e, Cat6, Cat7  ✓	Power	
Port mirroring		Power supply included *	<b>✓</b>
IP routing		Number of power supply units	1
Flow control support	✓	AC input voltage	120 - 230 V
Link aggregation	✓	Power consumption (max)	49 W
Rate limiting	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	×
Spanning tree protocol	✓		^
Auto-sensing	✓	Operational conditions	
Auto-negotiation	✓	Operating temperature (T-T)	0 - 50 °C
VLAN support	✓	Storage temperature (T-T)  Operating relative humidity (H-H)	-20 - 70 °C 0 - 90%
Virtual LAN features	Private VLAN	Storage relative humidity (H-H)	0 - 95%
Optical fiber		Operating altitude	0 - 3000 m
Fiber ethernet cabling technology	10GBASE-LR, 10GBASE-LRM, 10GBASE-SR	Non-operating altitude Heat dissipation	0 - 3000 m 18577 BTU/h

Data transmission		Weight & dimensions	
Switching capacity * 320 Gbit/s  Forwarding rate 357 Mpps  MAC address table * 16000 entries  Store-and-forward   Number of static routes 64	Width Depth Height Weight  Packaging content	212 mm 345 mm 44 mm 3.32 kg	
Jumbo frames support Jumbo frames Security	9000	Cables included User guide Rack mount kit	AC, LAN (RJ-45), Mini-USB
DHCP features Access Control List (ACL) Security algorithms SSH/SSL support	DHCP server, DHCP client  ✓  HTTPS, SNMP, SSH	Packaging data Rubber feet Resource CD	<i>'</i>
BPDU filtering/protection  Multicast features  Multicast support	✓ ✓	Logistics data  Harmonized System (HS) code	85176990





606449110005

0606449110005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.