StarTech.com

StarTech.com Mini USB Bluetooth 4.0 Adapter - 50m (165ft) Class 1 EDR Wireless Dongle

Brand : StarTech.com

Product code: USBBT1EDR4

Product name : Mini USB Bluetooth 4.0 Adapter - 50m (165ft) Class 1 EDR Wireless Dongle

StarTech.com Bluetooth Adapter - Mini Bluetooth 4.0 USB Adapter - 50m/165ft Wireless Bluetooth Dongle - Smart Ready LE+EDR (USBBT1EDR4)
StarTech.com Mini USB Bluetooth 4.0 Adapter - 50m (165ft) Class 1 EDR Wireless Dongle. Connectivity technology: Wireless, Host interface: USB, Interface: Bluetooth. Maximum data transfer rate: 3 Mbit/s, Wi-Fi band: Single-band (2.4 GHz). Product colour: Black

Ports & interfaces

Connectivity technology *	Wireless
Host interface *	USB
Interface *	Bluetooth

Network

Maximum data transfer rate *	3 Mbit/s
Wi-Fi band	Single-band (2.4 GHz)
Frequency range	2.402 - 2.48 GHz
Modulation	DQPSK, GFSK
Maximum operating distance	50 m
Bluetooth	✔
Bluetooth version	4.0+EDR

Design

Product colour	Black
Internal *	✘
Chipset	CSR8510A10
LED indicators	Link, Power, Stand-by

Operational conditions

Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 75%

Sustainability

Sustainability compliance	✔

Weight & dimensions

Width	14.4 mm
Depth	21.9 mm
Height	8 mm
Weight	2 g

Packaging data

Package width	173 mm
Package depth	134 mm
Package height	33 mm
Package weight	56 g

Packaging content

Manual	✔

Technical details

Compliance certificates	CE, RoHS

Logistics data

Harmonized System (HS) code	85176990
Master (outer) case width	309 mm
Master (outer) case length	490 mm
Master (outer) case height	426 mm
Products per master (outer) case	60 pc(s)

System requirements

|	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS 9.0, Mac OS 9.1, Mac OS 9.2, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019

Operational conditions

Operating temperature (T-T)	-10 - 50 °C

0065030852920

065030852920

0758399150201

758399150201