Epson Expression 13000XL Flatbed scanner 2400 x 4800 DPI A3 White

Brand : Epson **Product code:** B11B257401BY

Product name: Expression 13000XL

- A3 graphics scanner
- High precision
- Powerful software
- Optional TPU

A3, 2400 x 4800 DPI, 3.8 Dmax, 16/48 Bits Color, ReadyScan LED technology, 656 x 458 x 158 mm, 14.3 kg $\,$

Epson Expression 13000XL. Maximum scan size: 310 x 437 mm, Optical scanning resolution: 2400 x 4800 DPI, Input colour depth: 48 bit. Scanner type: Flatbed scanner, Product colour: White. Light source: ReadyScan LED, Scanning noise level: 60 dB. Maximum ISO A-series paper size: A3, ISO A-series sizes (A0...A9): A3, A4, A5, ISO B-series sizes (B0...B9): B4, B5. Width: 656 mm, Depth: 458 mm, Height: 158 mm

Scanning		Ports & interfaces	
Maximum scan size * Optical scanning resolution * Duplex scanning * Input colour depth Output colour depth Input greyscale depth Output greyscale depth Scan speed (b/w, low res, A4) Scan speed (colour, low res, A4)	310 x 437 mm 2400 x 4800 DPI 48 bit 48 bit 16 bit 16 bit 12 sec/page 12 sec/page	USB port *	✓
		USB version	2.0
		Weight & dimensions	
		Width	656 mm
		Depth	458 mm
		Height	158 mm
		Weight	14.3 kg
		Packaging data	
Design		Quantity per pack	1 pc(s)
Scanner type * Flatbed scanner Product colour * White Built-in display * X	Flatbed scanner	System requirements	
		Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows Vista, Windows XP
Performance			Mac OS X 10.10 Yosemite, Mac OS X
Light source Scanning noise level	ReadyScan LED 60 dB	Mac operating systems supported	10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Paper handling			Windows Server 2003. Windows
Maximum ISO A-series paper size * ISO A-series sizes (A0A9)	A3 A3, A4, A5	Server operating systems supported	Server 2008, Windows Server 2008 R2, Windows Server 2012 R2
ISO B-series sizes (B0B9)	B4, B5	Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C -25 - 60 °C 10 - 80%
		Storage relative humidity (H-H)	10 - 85%



