





+40% of DYMO<sup>®</sup> labels are produced<sup>\*</sup> using "Water based solvents".



DYMO<sup>®</sup> high quality labels are made in Belgium D1

## **D1 Standard Polyester Labels**

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking. Temperature rating: -18°C to  $90^{\circ}C$ 

| D1 STANDARD LABELS (7 m)     | 6 mm     | 9 mm     | 12 mm    | 19 mm    |
|------------------------------|----------|----------|----------|----------|
| ABC                          | S0720780 | S0720680 | S0720530 | S0720830 |
| ABC                          | S0720770 | S0720670 | S0720500 | S0720820 |
| ABC                          | S0720790 | S0720730 | S0720580 | S0720880 |
| ABC                          | -        | S0720710 | S0720560 | S0720860 |
| ABC                          | -        | S0720740 | S0720590 | S0720890 |
| ABC                          | -        | S0720720 | S0720570 | S0720870 |
| ABC                          | -        | -        | S0720610 | S0720910 |
| ABC                          | -        | S0720690 | S0720540 | S0720840 |
| ABC                          | -        | -        | S0720510 | -        |
|                              | -        | -        | S0720600 | -        |
| ABC                          | -        | S0720700 | S0720550 | S0720850 |
| ABC                          | -        | -        | S0720520 | -        |
| D1 STANDARD MULTIPACKS (7 m) | 6 mm     | 9 mm     | 12 mm    | 19 mm    |
| ABC                          | -        | 2093096  | 2093097  | 2093098  |





## **D1 Durable Vinyl Labels**

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces. Temperature rating: -40°C to  $80^\circ\text{C}$ 

| D1 DURABLE LABELS (3 m)   | 12 mm   |
|---------------------------|---------|
| ABC                       | 1978366 |
| ABC                       | 1978365 |
| ABC                       | 1978367 |
| D1 DURABLE LABELS (5.5 m) | 12 mm   |
| ABC                       | 1978364 |

## **D1 Permanent Polyester Labels**

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more. Temperature rating: -40°C to  $150^{\circ}C^{*}$ 

| D1 PERMANENT POLYESTER (5.5 m) | 12 mm    | 19 mm    |
|--------------------------------|----------|----------|
| ABC                            | S0718060 | S0718050 |

\*depends on surface

## **D1 Flexible Nylon Labels**

Specifically designed for curved surfaces and wire and cable marking. Temperature rating:  $-40^{\circ}$ C to  $60^{\circ}$ C

| D1 FLEXIBLE NYLON (3.5 m) | 12 mm    | 19 mm    |
|---------------------------|----------|----------|
| ABC                       | S0718040 | S0718070 |

The DYMO<sup>®</sup> high quality labels are made in Belgium











This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.