

Philips Signage Solutions 37BDL3050S/00 Signage Display 94 cm (37") 700 cd/m² Full HD Black Built-in processor Android 8.0 24/7

Brand : Philips

Product family: Signage Solutions

Product code: 37BDL3050S/00



Product name : 37BDL3050S/00

Philips Signage Solutions 37BDL3050S/00. Display diagonal: 94 cm (37"), Display resolution: 1920 x 540 pixels, Display brightness: 700 cd/m², HD type: Full HD. Operating hours (hours/days): 24/7. Operating system installed: Android 8.0. Product colour: Black

Display		Performance	
Display diagonal *	94 cm (37")	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Display resolution *	1920 x 540 pixels		
Display brightness *	700 cd/m²		
HD type *	Full HD		
Native aspect ratio	32:9		
Response time	8 ms	Operating hours (hours/days)	24/7
Contrast ratio (typical)	4000:1	Mean time between failures (MTBF)	50000 h
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	70 W
Pixel pitch	0.47 x 0.47 mm	Power consumption (standby) *	0.5 W
Ports & interfaces		Input voltage	100/240 V
HDMI ports quantity *	2	AC input voltage	100/240 V
HDMI version	2.0	AC input frequency	50 - 60 Hz
HDMI input ports quantity	1	Computer system	
HDMI output ports quantity	1	Built-in processor *	✓
VGA (D-Sub) input ports	1	Internal memory	2 GB
USB port *	✓	On-board graphics card model	ARM Mali-G51
USB ports quantity	1	Internal storage capacity	8 GB
USB version	2.0	Operating system installed	Android 8.0
USB connector type	USB Type-A	Weight & dimensions	
Ethernet LAN *	✓	Display width	928.5 mm
Ethernet LAN (RJ-45) ports	1	Display depth	48.7 mm
PC Audio in	✓	Display height	282.3 mm
RS-232 interface	✓	Display weight	7.76 kg
Remote (IR) input	1	Packaging content	
Remote (IR) output	1	Remote control included	✓
Design		Batteries included	✓
Placement supported *	Indoor	Cables included	AC, HDMI, IR sensor, RS-232
Orientation	Horizontal	Mounting kit	✓
Product colour *	Black	Operational conditions	
VESA mounting *	✓	Operating temperature (T-T)	0 - 40 °C
Panel mounting interface	400 x 200 mm	Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	-20 - 60 °C
		Storage relative humidity (H-H)	5 - 95%
Certificates			
		Certification	THIS FCC Class A CB



8712581799489



0810112790016



810112790016

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.