

HT240CUA

60,4 cm / 23.8" Diagonal
LED Backlight – Format 16:9

- 23,8" Touch Monitor LED Backlight
- 1920 x1080 @ 100Hz Full HD Resolutic
- 10 Points P-Cap Touch
- Optical Bonding / Full Lamination
- MPP2.0 Support (Microsoft Pen Protoc
- Anti-Glare Panel Surface
- Edge to Edge Glass Design
- 178° / 178° Ultra Wide Viewing Angle
- HDMI + DP + VGA Inputs
- USB Type-C input (signal and touch)
- USB 3.0 HUB
- Built-In Stereo Speakers
- Wall-Mountable (VESA)
- Smart adjustable book-stand
- Tilt Angle:15°~70°



60,4 cm / 23.8"

Part No.: HT240CUA



23.8"
16:9 Aspect Ratio



VGA
HDMI
DP



178° Ultra-Wide
Viewing Angle



10 Point
Touch



MPP2.0
Support



Full HD
1920 x 1080



Type-C



VESA
Wall-Mountable



Anti
Glare



Optical
Bonding

Display Size	60,4 cm / 23.8" Diagonal
Panel Type	TFT – LED Backlight, VA Panel (*)
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness (Typical)	270 cd/m ² (Monitor) with touch
Contrast	4.000:1 (Typical); 10.000.000:1 (Active)
Viewing Angle L/R; U/D	178° H – 178° V (CR >10)
Response Time	6 msec (with OD)
Pixel Pitch	0,2745 (H) x 0,2745 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Optical Bonding (Full Lamination)
Panel Surface	Glossiness: 60±20%; Roughness: <0.25µm
Glass Hardness / Thickness	7H Toughened glass panel surface / 1.1±0.05 mm
Touch Interface	USB-B; Type-C. Support MPP2.0 (Microsoft Pen Protocol)
Supported operating systems	Windows; Linux; Android; Mac OS (Single Touch point, Driver required **)
Display Colors	16.7M Colors
Frequency	Horizontal : 30~120 kHz (HDMI/DP/Type-C); 30~83 kHz (VGA) Vertical : 48~100Hz (HDMI/DP/Type-C); 56~75 Hz (VGA)
Max Display Frequency	1920 x 1080 @ 100Hz (HDMI/DP/Type-C); 60Hz (VGA)
Input 1, 2, 3	HDMI (Ver. 1.4); Display Port (Ver. 1.2); D-Sub (VGA)
Input 4	Type C (for Signal and Touch. Without Power Delivery, output voltage 5V 0.6A)
Input 5	PC Audio line in
USB HUB	USB 3.0: USB-B x 1; USB-A x 2
Built-in Speakers	Yes, 2W x 2; Earphone jack
Power Consumption	On: 13W; Stand-by: 0,26W; Off: 0,18W
Power Supply	External Power Supply: DC 12 Volt / 3A Input: AC 100 ~ 240 Volt; 50 ~ 60 Hz
Net / Gross Weight	4,07 Kg / 5,63 Kg

Product Dimensions	549,8 x 49,2 x 333,2 mm (W x D x H)
Packing Dimensions	647 x 138 x 426 mm (W x D x H)
VESA Mounting	100 x 100 mm
Monitor Stand	Smart Adjustable Stand ("book" type)
Tilt / Kensington Lock	15° ~ 70° / Yes
Controls	Menu / ▲ (Bri) / ▼ (Vol) / Return(Input) / Power
Color	Warm, Natural, Cool, User Mode
Preset Mode	Standard, Text, Game, Movie Mode
On Screen Display	10 OSD Languages
Accessory	Power Supply; Power Cable (1,5m); HDMI Cable (1,5m); USB A-B Cable (1,8m); Warranty Card; Quick Start Guide
Orientation	Landscape, Portrait

Supplier's Name	HANNspree
Model Name	HT240CUA
Energy efficiency class for standard Dynamic Range (SDR)	D
Annual Energy Power Consumption (kWh/1000h)	13 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	13 W
Off mode power demand (W)	≤ 0.3 W
Standby mode power demand (W)	≤ 0.5W
Screen Diagonal (cm / inches)	60,4 cm / 23.8"
Resolution	1920 x 1080

PART NO.: HT240CUA	EAN CODE 4711404024719
-----------------------	---------------------------

* "VA" word mark / trademark and related patents on technologies belong to their respective owners.

** For more details contact your local HANNspree office / representative or send us a request via the product enquiry form on the website.

Display Solutions



