



APC Smart-UPS RT 1000VA 230V - Marine

Brand : APC

Product code: SURT1000XLIM

Product name : Smart-UPS RT 1000VA 230V - Marine



Smart-UPS RT 1000VA 230V - Marine

APC Smart-UPS RT 1000VA 230V - Marine:

High availability, ruggedized power protection for shipboard and other transportation applications.
APC Smart-UPS RT 1000VA 230V - Marine. Output power capacity: 1 kVA, Output power: 700 W, Input operation voltage (min): 100 V. AC outlet types: C13 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 85 mm, Depth: 483 mm, Height: 432 mm

| Features | | Design | |
|--|-------------------------|-----------------------------------|--|
| Output power capacity * | 1 kVA | Cable length | 2.5 m |
| Output power * | 700 W | Product colour * | Black |
| Input operation voltage (min) * | 100 V | LED indicators | ✓ |
| Input operation voltage (max) * | 280 V | Certification | CE, DNV, EN 50091-1, EN 50091-2, EN 55022 Cl. A, EN 60950, EN 61000-3-2. |
| Input frequency * | 50/60 Hz | Operational conditions | |
| Output operation voltage (min) | 220 V | Operating temperature (T-T) | 0 - 55 °C |
| Output operation voltage (max) | 240 V | Storage temperature (T-T) | -20 - 50 °C |
| Surge energy rating | 420 J | Operating relative humidity (H-H) | 0 - 95% |
| Efficiency | 88% | Storage relative humidity (H-H) | 0 - 95% |
| Crest factor | 3:1 | Operating altitude | 0 - 3000 m |
| Emergency Power Off (EPO) | ✓ | Non-operating altitude | 0 - 15000 m |
| Output voltage Total Harmonic Distortion (THD) | 3% | Technical details | |
| Noise level | 55 dB | Compliance certificates | RoHS |
| Ports & interfaces | | Weight & dimensions | |
| AC outlet types | C13 coupler | Width | 85 mm |
| AC outlets quantity | 8 AC outlet(s) | Depth | 483 mm |
| Number of output IEC jumpers | 2 | Height | 432 mm |
| RS-232 ports | 1 | Weight | 23 kg |
| Battery | | Package weight | 27.8 kg |
| Battery technology | Sealed Lead Acid (VRLA) | Logistics data | |
| Battery recharge time | 3 h | Harmonized System (HS) code | 85078000 |
| Design | | Other features | |
| Form factor * | Rackmount | Dimensions (WxDxH) | 85 x 483 x 432 mm |
| Rack capacity | 2U | Nominal output voltage | 230 V |
| | | Nominal input voltage | 230 V |
| | | Package dimensions (WxDxH) | 630 x 594 x 286 mm |



0731304283515



731304283515

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.