

# Specifications

Photo is representative

## Eaton 9PX11KIRTNG2

Eaton 9PX Gen2 UPS Netpack, 11000 VA, 11000 W, Input: Hardwired, Outputs: (8) C13, (8) C39, Hardwired, Rack/tower, 4U, Gigabit Network card included, Rack-mounting kit included

### General specifications

<b>PRODUCT NAME</b>	Eaton 9PX Gen2 UPS
<b>CATALOG NUMBER</b>	9PX11KIRTNG2
<b>MODEL CODE</b>	Eaton 9PX 11000i RT4U Netpack G2
<b>EAN</b>	3553340710612
<b>UPC</b>	786689812072
<b>PRODUCT LENGTH/DEPTH</b>	724 mm
<b>PRODUCT HEIGHT</b>	174 mm
<b>PRODUCT WIDTH</b>	440 mm
<b>PRODUCT WEIGHT</b>	78.8 kg
<b>WARRANTY</b>	3 year on electronics, 2 year on battery
<b>COMPLIANCES</b>	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
<b>CERTIFICATIONS</b>	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM

## Battery

<b>BATTERY TYPE</b>	Sealed, lead-acid
<b>RUNTIME GRAPH</b>	View runtime graph
<b>BATTERY QUANTITY</b>	20
<b>BATTERY MANAGEMENT</b>	<ul style="list-style-type: none"><li>• ABM+ (Predictive battery life) &amp; Temperature compensated charging method (user selectable)</li><li>• Automatic battery test</li><li>• Deep discharge protection</li><li>• Automatic recognition of external battery units</li></ul>
<b>BATTERY RATING</b>	12 V / 9 Ah
<b>EXTENDED BATTERY CAPABILITY</b>	Yes

## Electrical input

<b>NOMINAL FREQUENCY</b>	50/60 Hz
<b>INPUT POWER FACTOR</b>	>.99
<b>INPUT VOLTAGE RANGE</b>	176-276 V (100-276 V with derating)
<b>INPUT FREQUENCY RANGE</b>	40-70 Hz

## Electrical output

<b>RECEPTACLE</b>	(8) C13, (8) C39, Hardwired
<b>VOLTAGE</b>	230V
<b>VA RATING</b>	11 kVA
<b>WATTAGE</b>	11 kW
<b>OUTPUT POWER FACTOR</b>	1
<b>OUTPUT VOLTAGE RANGE</b>	200/208/220/230/240 V +/- 1%
<b>OUTPUT WAVEFORM</b>	Sine wave
<b>OUTPUT NOMINAL VOLTAGE</b>	230V default (200/208/220/230/240V)
<b>VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX</b>	1
<b>FEED TYPE</b>	1
<b>TOPOLOGY</b>	Online/Double-conversion

## Communications

<b>INCLUDES NETWORK CARD</b>	Yes
<b>COMMUNICATION</b>	<ul style="list-style-type: none"><li>• USB port (HID compliant)</li><li>• Serial port (RS232)</li><li>• Mini terminal block for remote On/Off</li><li>• Mini-terminal block for remote power off</li><li>• Mini-terminal block for dry contacts outputs (2 contacts)</li><li>• Network card</li></ul>
<b>ETHERNET INTERFACE</b>	Yes
<b>USER INTERFACE</b>	Multilingual graphical LCD display
<b>POTENTIAL FREE SWITCH CONTACT</b>	Yes
<b>EXPANSION SLOTS</b>	2 slots, network card included
<b>SOFTWARE</b>	Eaton Brighthouse

Environmental	
ALTITUDE	3000 m
NOISE LEVEL	<37 dB at 1 meter
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	0-95% non-condensing

COMPATIBILITY	Software suite
TYPE OF INTERFACE	Other

Additional specifications	
CONSTRUCTION TYPE	482.6 mm (19 inch) device
PACKAGE CONTENTS	<ul style="list-style-type: none"> <li>• UPS</li> <li>• (3) cable glands</li> <li>• (2) IEC-IEC output cables (1,2m)</li> <li>• USB cable (1,8m)</li> <li>• Network Management Card</li> <li>• Supports for tower mounting</li> <li>• Rack-mounting kit with brackets and slides for UPS</li> <li>• Safety instructions</li> <li>• Quickstart guide</li> </ul>
INTERNAL BYPASS	Yes
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black/silver
EFFICIENCY	97
RACK MOUNTING KIT	Yes
HOT SWAP POWER	No

Resources	
BROCHURES	<a href="#">Eaton 9PX Gen2 EMEA Brochure - EN</a>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



**Eaton Corporation plc**  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.