

## **DELL UltraSharp 24 Monitor - U2422H**

Brand : DELL Product family: UltraSharp Product code: DELL-U2422H

Product name : Dell

UltraSharp 24 Monitor - U2422H

- 60.47cm (23.8") Full HD 1920 x 1080 W-LED IPS
- 8ms, 16:9, 250cd/m<sup>2</sup>, 1000:1
- USB, HDMI, DisplayPort

60.47cm (23.8") Full HD 1920 x 1080 W-LED IPS, 16:9, 250cd/m<sup>2</sup>, 16.78M, 8ms, 1000:1

## DELL UltraSharp 24 Monitor - U2422H:

Elevate your productivity on this innovative 24-inch FHD monitor that delivers wide color coverage and fast connectivity.

DELL UltraSharp 24 Monitor – U2422H. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal:  $178^\circ$ , Viewing angle, vertical:  $178^\circ$ . Built-in USB hub. VESA mounting, Height adjustment. Product colour: Silver







Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio *	60.5 cm (23.8") 1920 x 1080 pixels Full HD 16:9	Cable lock slot * Height adjustment * Height adjustment Pivot	√ √ 15 cm √
Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical)	LCD IPS W-LED  X 250 cd/m <sup>2</sup>	Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range	-90 - 90°
Response time * Anti-glare screen Screen shape * Supported graphics resolutions	8 ms  Flat  640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080)	Power  Energy efficiency class (SDR) *  Energy efficiency class (HDR) *  Energy consumption (SDR) per 1000 hours *  Power consumption (typical) *  Power consumption (standby) *	C Not available 12 kWh 11.6 W 0.3 W
Supported video modes  Contrast ratio (typical) *  Maximum refresh rate *  Viewing angle, horizontal  Viewing angle, vertical  Display number of colours *  Response time (fast)  Pixel pitch	480i, 480p, 576i, 576p, 720p, 1080i, 1080p 1000:1 60 Hz 178° 178° 16.78 million colours 5 ms 0.2745 x 0.2745 mm 92.53 ppi		63 W 0.3 W 11.06 W 100 - 240 V 50 - 60 Hz 1.2 A Internal A to G 414164
Horizontal scan range Vertical scan range Viewable size, horizontal	30 - 83 kHz 56 - 76 Hz 52.7 cm	Operational conditions Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C

Display		Operational conditions	
Viewable size, vertical Viewable size diagonal	29.6 cm 60.5 cm	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 80% 5 - 90%
Display diagonal (metric)	60.47 cm	Weight & dimensions	
High Dynamic Range (HDR) supported Colour gamut standard Colour gamut	SRGB 100%	Width (with stand) Depth (with stand) Height (with stand)	537.6 mm 179.6 mm 496 mm
Performance		Weight (with stand) Width (without stand)	5.27 kg 537.6 mm
NVIDIA G-SYNC * AMD FreeSync *	×	Depth (without stand) Height (without stand)	48.5 mm 310.7 mm
Multimedia		Weight (without stand)	3.52 kg
Built-in speaker(s) * Built-in camera *	×	Bezel width (side) Bezel width (top) Bezel width (bottom)	5.3 mm 5.3 mm 8.95 mm
Design			0.93 111111
Market positioning *	Business	Packaging data Package weight	7.82 kg
Product colour * Front bezel colour	Silver Black	5 5	7.82 kg
Feet colour	Silver	Carbon footprint	470
Ports & interfaces		Total carbon footprint (kg of CO2e)  Total carbon emissions, standard	479
Built-in USB hub *	<b>√</b>	deviation (kg of CO2e)	99
USB upstream port type	USB Type-C	Carbon emissions, manufacturing (kg of CO2e)	339
Number of upstream ports	1	Carbon emissions, logistics (kg of	39
Number of USB Type-C upstream ports quantity	1	CO2e) Carbon emissions, energy usage (kg	
USB Type-A downstream ports quantity	3	of CO2e) Carbon emissions, end-of-life (kg of	
USB Type-C downstream ports	1	CO2e)	3
quantity HDMI *	<b>√</b>	Total carbon emissions, w/o use phase (kg of CO2e)	381
HDMI ports quantity	1	Logistics data	
HDMI version	1.4	Harmonized System (HS) code	85285210
DisplayPorts quantity DisplayPort version	2 1.4		
Audio output	<b>√</b>		
Charging port type	USB Type-A		
Network			
Wi-Fi	x		
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		





5397184504970

5704174556756

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.