



F1DN104B-3



F1DN104C-3



F1DN104E-3



F1DN104F-3

BELKIN SECURE DVI-I 4-PORT KVM SWITCH

SECURE | CERTIFIED | CONNECTED

Secure DVI-I KVM Switch

The Belkin Secure KVM Switch is designed for use in defense and intelligence installations requiring consolidated control between computers running at different security enclaves and provides the stringent safeguards required by today's IA (Information Assurance) computing requirements.

The Belkin Secure DVI-I KVMs support DVI-I dual-link inputs/outputs for up to 4K (3840 x 2160 pixels) at 30Hz video resolutions and can support inputs from both digital and analog (VGA) sources.

Certified to the NIAP PP3.0 certification and assurance standard, users can confidently leverage the same set of monitors and PC peripherals to streamline work flows and enhance efficiencies in working across disparate systems and security enclaves without introducing pathways for cybersecurity threats to migrate from one system to the next. The Belkin Secure KVM maintains true air-gap isolation by emulating video EDID and USB communication between inputs and outputs. Further, optical data diodes on all USB connections assure uni-directional data flow of HID filtered information with no signal leakage between channels. Dedicated Common Access Card (CAC) input ports on the F1DN104C-3 and F1DN104F-3 consolidate the number of CAC readers and allow a single reader to be shared across all 4 systems for user authentication.

Integrated anti-tamper switches protected by an always-on battery backup system immediately render the unit permanently inoperable in the event of a breach attempt. Unique mechanical design accommodates desktop or under-desk mounting with optional bracket along with an optional remote-control capability to further declutter the operator's desk.



KEY FEATURES AND BENEFITS

- Certified for Use on Government and Military Networks**
 Certified for NIAP Protection Profile PSS 3.0.
- TAA Compliant**
 Assembled in the USA, US-based technical support, secure packaging ensures integrity from factory to user site.
- Compatible with DVI-I Graphic Cards**
 Supports single-link and dual-link DVI-I; VGA and HDMI input/output supported via compatible cables.
- High Resolution Video**
 Support for up to UHD 4K: Up to 3840 x 2160 @ 30 Hz
- Models:**
 Choose the model that suits you best.
 - F1DN104B-3**
 Single-Head, 4-port DVI-I KVM, with Audio
 - F1DN104C-3**
 Single-Head, 4-port DVI-I KVM, with Audio and CAC port.
 - F1DN104E-3**
 Dual-Head, 4-port DVI-I KVM, with Audio
 - F1DN104F-3**
 Dual-Head, 4-port DVI-I KVM, with Audio and CAC port.



All Belkin Secure KVMs are designed and assembled in the United States and shipped in tear-away packaging, preserving cyber assurance from factory to installation at the end site. US-based technical support and a standard 3-year warranty with options for up to 5 years of coverage provide unsurpassed customer support. The Belkin DVI-I Secure KVM represents the ideal solution against today's cyber threats for mission-critical applications in government, military, financial, healthcare, energy, and any application seeking guaranteed isolation between systems at the operator's desk.

NIAP CERTIFIED TO COMMON CRITERIA PROTECTION PROFILE PSS VER 3.0

This Belkin product is certified by NIAP to the latest Common Criteria Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.

Front and Rear Panel Views



F1DN104B-3



F1DN104C-3



F1DN104E-3



F1DN104F-3



SECURE | CERTIFIED | CONNECTED

Belkin Secure 4-Port DVI-I KVM Switch



PART NUMBER	F1DN104B-3	F1DN104C-3	F1DN104E-3	F1DN104F-3
No. of Computers	4	4	4	4
No. of Displays	1	1	2	2
Max Resolutions Supported	3840 x 2160 pixels (UHD 4K) @ 30Hz, 2560 x 1600 pixels @ 60Hz			
CONSOLE PORTS (DEVICES)				
Console Keyboard/Mouse Ports	USB Type-A female connector or PS/2 Mini-DIN 6-pin female connector (1 designated port for mouse and 1 designated port for keyboard)			
Console Display Ports	1x DVI-I Dual-Link	1x DVI-I Dual-Link	2x DVI-I Dual-Link	2x DVI-I Dual-Link
Console Audio Jack	1/8" (3.5mm) female			
Console CAC	N/A	USB Type A	N/A	USB Type A
DCU Port	RJ25			
COMPUTER PORTS				
Computer Display Ports	4x DVI-I Dual-Link female	4x DVI-I Dual-Link female	8x DVI-I Dual-Link female	8x DVI-I Dual-Link female
Computer Audio Jack	1/8" (3.5mm) female			
Computer Keyboard/Mouse Ports	USB Type B			
Computer CAC Ports	N/A	USB Type B	N/A	USB Type B
PHYSICAL				
Dimensions	12.6 (W) x 1.74 (H) x 6.2 (L) in 320 (W) x 44.2 (H) x 157.5 (L) mm	12.6 (W) x 1.74 (H) x 6.2 (L) in 320 (W) x 44.2 (H) x 157.5 (L) mm	12.6 (W) x 2.5 (H) x 6.2 (L) in 320 (W) x 44.2 (H) x 157.5 (L) mm	12.6 (W) x 2.5 (H) x 6.2 (L) in 320 (W) x 44.2 (H) x 157.5 (L) mm
Weight	3.8 lbs.(1.7 kg.)	3.8 lbs. (1.72 kg.)	4.725 lbs. (2.14 kg.)	4.765 lbs. (2.16 kg.)
POWER				
Power Requirements	12V 1.5A DC Power Supply			
AC Input	100 to 240VAC			
Power Type	External			
ENVIRONMENTAL				
Operating Temperature	32° to 104° F (0° to 40° C)			
Storage Temperature	-4° to 140° F (-20° to 60° C)			
Humidity Storage & Use	0-80% RH, non-condensing			
CERTIFICATION				
Security Accreditation	NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4.			
Regulatory Compliance	FCC Class B, UL, CE, RoHS, ICES, RCM			
GENERAL INFORMATION				
Made In	Designed in California. Assembled in US with US-based technical support (TAA compliant).			
Product Life-Cycle	5 years			
Warranty	3 years Standard (upgradeable to 4 or 5 years)			
Enclosure	Heavy-duty aluminum enclosure with metal faceplate.			



SECURE | CERTIFIED | CONNECTED

Belkin Secure 4-Port DVI-I KVM Switch

Recommended Cable Solutions

SKVM PC CONNECTION COMBO CABLES	PART NUMBER	DESCRIPTION
Video/Keyboard/Mouse/Audio	F1D9012b06 F1D9012b10	DVI-D, USB A/B plus Audio combo cable, 6' DVI-D, USB A/B plus Audio combo cable, 10'
Dual-Monitor Video/Keyboard/Mouse/Audio	F1D9014b06 F1D9014b10	Dual Monitor DVI-D, USB A/B plus Audio combo cable, 6' Dual Monitor DVI-D, USB A/B plus Audio combo cable, 10'
CAC Reader Cable	F1D9013b06 F1D9013b10	USB A/B cable, 6' USB A/B cable, 10'

Accessories and Optional Service Items

PART NUMBER	DESCRIPTION
0401-00348	Replacement Power Adapter, 12V/1.5A, North America
0401-00431	Replacement Power Adapter, 12V/1.5A, EU
0401-00432	Replacement Power Adapter, 12V/1.5A, UK
F1DN002R	Advanced Secure LCD Desktop Controller for 2 or 4 Port SKVM
F1D006	Mounting Bracket for F1DN102KVM-UN-3, F1DN202KVM-UN-3, F1DN104KVM-UN-3, F1DN104B-3, F1DN104C-3, F1DN104P-3, F1DN104K-3 or F1DN204M-3
F1D008	Mounting Bracket for F1DN104E-3, F1DN104F-3, F1DN104W-3, F1DN204KVM-UN-3, F1DN104Q-3
F1D005U	USB Smart Card/CAC Reader

Learn more at belkin.com/cybersecurity