Epson WorkForce DS-32000 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Epson **Product code:** B11B255401BY

Product name : WorkForce DS-32000

- High-volume scanning: 90ppm/180ipm & 40,000 daily duty cycles
- Adjustable chassis design: Normal, Horizontal and Compact options to suit your space
- Media versatility: Scan passports and bound media up to 6mm in thickness
- Control and security: Advanced paper handing with paper-protection sensors
- A4 and A3 flatbed options: Scan books and bound media with optional flatbed scanners

90ppm, 180ipm, 40000 daily duty cycles, 300 dpi, AC 100 V - 240 V, 5.8 kg
Epson WorkForce DS-32000. Optical scanning resolution: 600 x 600 DPI, Input colour depth: 10 bit, Output colour depth: 8 bit. Scanner type: Sheet-fed scanner, Product colour: Black, White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 40000 pages. Auto document feeder (ADF) input capacity: 120 sheets. Maximum ISO A-series paper size: A3

Scanning	
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	10 bit
Output colour depth	8 bit
ADF scan speed (b/w, A4)	90 ppm

Design	
Scanner type *	Sheet-fed scanner
Product colour *	Black, White
Display	LCD
Display diagonal	6.86 cm (2.7")
Built-in display *	✔

Performance	
Sensor type *	CIS
Daily duty cycle (max) *	40000 pages

Input capacity	
Auto document feeder (ADF) input capacity	120 sheets

Paper handling	
Maximum ISO A-series paper size *	A3

Ports & interfaces	
USB port *	✔

Ports & interfaces	
USB version	3.2 Gen 1 (3.1 Gen 1)
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)

Power	
Power supply type *	AC
Power consumption (typical)	20 W
Power consumption (standby)	11 W
Power consumption (off)	0.1 W
Sleep mode	✔
Input voltage	100 - 240 V

Weight & dimensions	
Width	371 mm
Depth	208 mm
Height	219 mm
Weight	5.8 kg

Packaging content	
Manual	✔
AC adapter included	✔

Operational conditions	
Operating relative humidity (H-H)	15 - 80%
Storage relative humidity (H-H)	15 - 85%

Logistics data	
Harmonized System (HS) code	84716070

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-DEC-2024. Prints or copies of Information are only valid on the printed Publication date