



## TP-Link TL-SG1005P-PD network switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

**Brand :** TP-Link

**Product code:** TL-SG1005P-PD

**Product name :** TL-SG1005P-PD



- Powered by PoE+ +/PoE+/PoE
- Up to 66 W PoE Budget\*
- Long-Range PoE+ (250 m\*\*)
- PoE Auto Recovery
- Plug and Play
- Multicast Optimization
- Silent Operation
- Durable Metal Casing

5-Port Gigabit Desktop PoE+ Switch with 1-Port PoE++ In and 4-Port PoE+Out, 158x101x25 mm, 10Gbps TP-Link TL-SG1005P-PD. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u,.... Power over Ethernet (PoE). Wall mountable

Management features		Design	
Quality of Service (QoS) support	✓	LED indicators	✓
Ports & interfaces		Wall mountable	✓
Basic switching RJ-45 Ethernet ports quantity *	5	Certification	CE, FCC, RoHS
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Network		Fanless	✓
Networking standards *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power	
		Power source *	PoE
10G support *	✓	Power supply included *	✗
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power consumption (max)	68.59 W
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Power over Ethernet (PoE)	
Flow control support	✓	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) ports quantity	5
Auto-negotiation	✓	Total Power over Ethernet (PoE) budget	66 W
MAC address auto-learning supported	✓	Operational conditions	
MAC address auto-aging supported	✓	Operating temperature (T-T)	-30 - 70 °C
Data transmission		Storage temperature (T-T)	-40 - 70 °C
Switching capacity *	10 Gbit/s	Operating relative humidity (H-H)	10 - 90%
Forwarding rate	7.44 Mpps	Storage relative humidity (H-H)	5 - 90%
MAC address table *	2000 entries	Heat dissipation	233.206 BTU/h
Store-and-forward	✓	Weight & dimensions	
Security		Width	158 mm
IGMP snooping	✓	Depth	101 mm
Design		Height	25 mm
Product colour	Black	Packaging data	
		User guide	✓
		Package type	Box



4895252501117

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-SEP-2024. Prints or copies of Information are only valid on the printed Publication date