



APC NetShelter Metered Rack PDU, 0U, 3PH, 22kW 230V 32A or 17.3kW 230V 24A, x30 C13 and x12 C19 outlets, IEC 309 3P+N+PE cord

Brand : APC


Product code: AP8886

Product name : NetShelter Metered Rack PDU, 0U, 3PH, 22kW 230V 32A or 17.3kW 230V 24A, x30 C13 and x12 C19 outlets, IEC 309 3P+N+PE cord

NetShelter Metered Rack PDU, 0U, 3PH, 22kW 230V 32A or 17.3kW 230V 24A, x30 C13 and x12 C19 outlets, IEC 309 3P+N+PE cord
APC NetShelter Metered Rack PDU, 0U, 3PH, 22kW 230V 32A or 17.3kW 230V 24A, x30 C13 and x12 C19 outlets, IEC 309 3P+N+PE cord. PDU types: Metered, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 42 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 1.83 m, Certification: EN 55022 A,EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, VCCI A, VDE REACH: No SVHCs. Monitoring: Current, Power, Voltage. Nominal input voltage: 400 V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz



Design		Power	
PDU types *	Metered	Load capacity	22080 VA
Rack capacity *	0U	Maximum input current per phase	32 A
Mounting	Vertical	Power protection features	Overload
Product colour	Black	Maximum power	22000 W
Ports & interfaces		Weight & dimensions	
AC outlets quantity *	42 AC outlet(s)	Dimensions (WxDxH)	56 x 51 x 1829 mm
Power plug	IEC309	Weight	8.72 kg
AC outlet types *	C13 coupler, C19 coupler	Packaging data	
Output connections	30 x IEC 320 C13 12 x IEC 320 C19		
Features		Package dimensions (WxDxH)	170 x 112 x 2050 mm
LED indicators	✓	Package weight	11.6 kg
Cable length	1.83 m	Operational conditions	
Certification	EN 55022 A,EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, VCCI A, VDE REACH: No SVHCs		
		Operating temperature (T-T)	0 - 55 °C
		Storage temperature (T-T)	-25 - 65 °C
		Operating relative humidity (H-H)	5 - 95%
Management features		Storage relative humidity (H-H)	5 - 95%
Monitoring	Current, Power, Voltage	Operating altitude	0 - 3000 m
Power		Non-operating altitude	0 - 15000 m
Nominal input voltage *	400 V	Technical details	
AC input frequency	50 - 60 Hz		
Maximum current *	32 A		
Nominal output voltage	230 V		



0731304289937



731304289937

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.