APC

APC Smart-UPS SMT1000IC – 8x C13, USB, SmartConnect, 1000VA

Brand : APC

Product code: SMT1000IC

Product name : APC Smart-UPS SMT1000IC – 8x C13, USB, SmartConnect, 1000VA

APC Smart-UPS SMT1000IC – 8x C13, USB, SmartConnect, 1000VA
APC Smart-UPS SMT1000IC – 8x C13, USB, SmartConnect, 1000VA. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 700 W. AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 171 mm, Depth: 439 mm, Height: 219 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	1 kVA
Output power *	700 W
Waveform *	Sine
Input operation voltage (min) *	151 V
Input operation voltage (max) *	302 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	459 J
Response time	10 ms
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	41 dB
Surge protection	✔
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	✔
Temperature voltage compensation	✔

Ports & interfaces

AC outlet types	C13 coupler, IEC Jumpers
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	✔

Battery

Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔
Automatic battery test	✔
Cold start	✔
Replacement battery cartridge	RBC6

Design

Form factor *	Mini Tower
Product colour *	Black
Display type	LCD
LED indicators	✔
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Sustainability certificates	Green Premium
Compliance certificates	RoHS

Ports & interfaces

USB 2.0 ports quantity	1
USB port type	USB Type-A
Serial interface	✔
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)

Weight & dimensions

Width	171 mm
Depth	439 mm
Height	219 mm
Weight	18.9 kg
Package width	328 mm
Package depth	595 mm
Package height	376 mm
Package weight	22.8 kg

Packaging data

Cables included	RJ-45, USB cable
Quick installation guide	✔

Logistics data

Products per pallet	12 pc(s)
Harmonized System (HS) code	85078000

0731304332978

731304332978