ASUS PRIME B760-PLUS D4 Intel B760 LGA 1700 ATX

Brand: ASUS Product code: 90MB1CW0-M1EAY0

Product name: PRIME B760-PLUS D4

- Intel® LGA 1700 Socket: Ready for 13th and 12th Gen Intel® processors
- Ultrafast Connectivity: PCle 5.0, three PCle 4.0 M.2, Realtek 2.5Gb Ethernet, USB 3.2 Gen 2x2 Type-C®, front USB 3.2 Gen 1 Type-C® and Thunderbolt $^{\text{TM}}$ (USB4®) header support
- Comprehensive Cooling: VRM heatsinks, M.2 heatsink, PCH heatsink, hybrid fan headers and Fan Xpert 2+
- ASUS OptiMem: Careful routing of traces and vias to preserve signal integrity for improved memory stability
- Aura $\stackrel{\circ}{\text{Sync}}$ RGB Lighting: Onboard Addressable Gen 2 headers and Aura RGB header for RGB LED strips, easily synced with Aura Sync-capable hardware

Prime B760-PLUS D4, an Intel B760 LGA 1700 ATX motherboard with PCIe 5.0, three PCIe 4.0 M.2 slots, DDR4, Realtek 2.5Gb Ethernet, DisplayPort, VGA, HDMI, SATA 6 Gbps, USB 3.2 Gen 2x2 Type-C, front USB 3.2 Gen 1 Type-C, Thunderbolt (USB4) support, Aura Sync





| Processor | | | Internal I/O | |
|---|--|--|---|----------------------------|
| Processor manufacturer * | | Intel | Thunderbolt headers | 1 |
| Processor socket * | | LGA 1700 | 12V power connector | ✓ |
| | | Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9 LGA 1700 | RGB LED pin header | ✓ |
| Compatible processor series * | | | Rear panel I/O ports | |
| Supported processor sockets | | | USB 2.0 ports quantity * | 2 |
| Memory | | | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 1 |
| Supported memory types * Number of memory slots * Memory slots type Memory channels | DDR4-SDRAM 4 DIMM Dual-channel | | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 2 |
| ECC compatibility Supported memory clock speeds Supported memory clock speed | Non-ECC 2133,2400,2666,2800,2933,3000, MHz 5066 MHz | .3200,3333,3400,3466,3600,3733,4000,4266,4400,4600,4800,5000,5066 | USB 3.2 Gen 2x2 Type-C ports quantity | 1 |
| (max) Maximum internal memory * | 128 GB | | Ethernet LAN (RJ-45) ports * | 1 |
| Unbuffered memory | | | VGA (D-Sub) ports quantity * | 1 |
| Storage controllers | | | HDMI ports quantity * | 1 |
| Supported storage drive types | | HDD & SSD | HDMI version | 2.1 |
| Supported storage drive interfaces * | | M.2, SATA III | DisplayPorts quantity | 1 |
| Number of HDDs supported | | 4 | DisplayPort version | 1.4 |
| Number of storage drives supported | | 7 | Headphone outputs | 1 |
| RAID support | | ✓ | Line-in | ✓ |
| RAID levels | | 0, 1, 5, 10 | Network | |
| Graphics | | | Ethernet LAN | 1 |
| Parallel processing technology support * | | Not supported | Ethernet interface type Wi-Fi * | 2.5 Gigabit Ethernet |
| Internal I/O | | | VVI-I I · | × |
| USB 2.0 connectors * 2 | | | Features | |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | | 2 | Motherboard chipset * Audio output channels * | Intel B760 7.1 channels |
| Number of SATA III connectors * | | 4 | Component for * Motherboard form factor * | PC ATX |

| Internal I/O | | Features | |
|---|--------|---|----------------------------------|
| S/PDIF out connector Front panel audio connector | ✓ ✓ | Motherboard chipset family * Windows operating systems supported | Intel Windows 10 x64, Windows 11 |
| Front panel connector ATX Power connector (24-pin) | * | Expansion slots PCI Express x1 (Gen 3.x) slots | 2 |
| CPU fan connector Number of chassis fan connectors Peripheral (Molex) power connectors (4-pin) | 3 | PCI Express x16 (Gen 4.x) slots PCI Express x16 (Gen 5.x) slots Number of M.2 (M) slots | 1 1 3 |
| EPS power connector (8-pin) | ✓ | BIOS | |
| Number of COM connectors TPM connector | 1 | BIOS type * BIOS memory size | UEFI AMI 128 Mbit |
| | | Weight & dimensions | |
| | | Width Depth | 305 mm 244 mm |
| | | Packaging content | |
| | | Cables included | SATA |

