

Logitech Rally Bar Mini

Brand : Logitech

Product code: 991-000389

Product name : Rally Bar Mini



Rally Bar Mini
Logitech Rally Bar Mini. HD type: 4K Ultra HD, Supported video modes: 576p, 720p, 900p, 1440p, 2160p, Maximum frame rate: 30 fps. Digital zoom: 4x. Ethernet LAN, Wi-Fi. Display: IPS, Display diagonal: 25.6 cm (10.1"), Display resolution: 1280 x 800 pixels. Product colour: Graphite

| Performance | | Microphone | |
|---|--|---|---|
| Product colour * | Graphite | Microphone frequency | 90 - 16000 Hz |
| Pan range | -25 - 25° | Microphone direction type | Omnidirectional |
| Tilt angle range | -15 - 15° | Sound pressure level (max) | 90 dB |
| PTZ control | ✓ | Number of microphones | 6 |
| Video | | Features | |
| HD type * | 4K Ultra HD | Telepresence * | ✗ |
| Supported video modes | 576p, 720p, 900p, 1440p, 2160p | Motion sensor | ✓ |
| Maximum frame rate | 30 fps | Cable lock slot | ✓ |
| Audio | | Cable lock slot type | Kensington |
| Built-in speaker(s) | ✓ | Logistics data | |
| Output level | 92/99 dB | Master (outer) case gross weight | 8.87 kg |
| Line-out impedance | 4 Ω | Master (outer) case length | 808 mm |
| Output voltage Total Harmonic Distortion (THD) | 2% | Master (outer) case width | 258 mm |
| Audio beamforming | ✓ | Master (outer) case height | 302 mm |
| Noise reduction | ✓ | Harmonized System (HS) code | 85176990 |
| Echo cancellation | ✓ | Battery | |
| RMS rated power | 5 W | Battery capacity | 0.675 Wh |
| Microphone pick-up range | 4.5 m | Computer system | |
| Sample rates | 0 - 48 kHz | Windows operating systems supported | Windows 10, Windows 11 |
| Ports & interfaces | | Mac operating systems supported | Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey |
| HDMI ports quantity | 3 | Operational conditions | |
| HDMI output ports quantity | 2 | Operating temperature (T-T) | 0 - 40 °C |
| HDMI input ports quantity | 1 | Operating relative humidity (H-H) | 10 - 95% |
| USB connector type | USB Type-A, USB Type-C | Storage temperature (T-T) | -40 - 70 °C |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 3 | Heat dissipation | 64 BTU/h |
| Ethernet LAN (RJ-45) ports | 1 | Power | |
| DC-in jack | ✓ | Power source type | AC |
| Microphone in | ✓ | AC input voltage | 100 - 240 V |
| Interface module | | Current | 4.754 A |
| Interface module RJ-45 ports quantity | 1 | DC input voltage | 19 V |
| Network | | Battery technology | Lithium |
| Ethernet LAN * | ✓ | Battery capacity | 220 mAh |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Number of batteries supported | 2 |
| Wi-Fi | ✓ | Power plug type | Type G |
| Wi-Fi standards | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) | Weight & dimensions | |
| Supported network protocols | IPv4, IPv6 | Interface module dimensions (W x D x H) | 246.2 x 171.3 x 56.1 mm |
| Security algorithms | 128-bit AES | Interface module weight | 1 kg |

| Camera | | Weight & dimensions | |
|---------------------------|-------------------|-------------------------|--|
| Zoom capability | ✓ | Width | 719 mm |
| Digital zoom | 4x | Depth | 101 mm |
| Horizontal field of view | 113° | Height | 91.4 mm |
| Vertical field of view | 80.7° | Weight | 4.03 kg |
| Diagonal field of view | 120° | Package width | 252 mm |
| Remote control interface | Bluetooth | Package depth | 802 mm |
| Display | | Package height | 289 mm |
| Display | IPS | Package weight | 8.87 kg |
| Display diagonal | 25.6 cm (10.1") | Packaging content | |
| Display resolution | 1280 x 800 pixels | Cables included | AC, DC, HDMI, USB Type-A to USB Type-C |
| Contrast ratio (typical) | 1000:1 | Power cable length | 2.5 m |
| Touchscreen | ✓ | HDMI cable length | 2 m |
| Touchscreen type | Capacitive | AC adapter included | ✓ |
| Viewing angle, horizontal | 85° | Mounting kit | ✓ |
| Viewing angle, vertical | 85° | Remote control included | ✓ |
| Display brightness | 400 cd/m² | Camera included | ✓ |
| Oleophobic coating | ✓ | Quick start guide | ✓ |
| Microphone | | | |
| Microphone sensitivity | -36 dB | | |



5099206102149

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date