


Chief DVM0500U2 TiLED® dvLED Universal 500mm, 2 High Starter SKU: DVM0500U2



The next generation of TiLED® dvLED Wall Mounts is a patent-pending universal modular system that is compatible with a multitude of interlocking dvLED panels from leading manufacturers. New floating button-capture technology and mounting hardware streamlines specifying, ordering and installation. One set of part numbers can be ordered and stocked globally to fulfill a variety of video wall installation needs.

In this video series you will learn about all of the features

Universally compatible

of TiLED Universal Wall Mounts.

Thanks to new floating button-capture technology and universal mounting hardware, TiLED Series dvLED Universal Wall Mounts are compatible with 90% of interlocking dvLED panels from leading manufacturers such as Absen, Barco, Hikvision, INFiLED, LG, LianTronics, Philips, Planar, Samsung, Sharp/NEC, Sony, Unilumin and more.

Uneven walls? No problem

TiLED dvLED Universal Mounts provide total X-Y-Z axis adjustability to compensate for wall irregularities – resulting in precision pixel alignment for a flawless uniform display. No misaligned pixels or gaps, even with dvLED displays with pixel pitches below 1 mm. Because it's easy to fine-tune and adjust the position of each mount, installation time is greatly reduced, sometimes even from days to hours. Chief's new independent Y-axis adjustment at each panel edge helps set a flat and level base for your direct view LED video wall. Double-depth Z-axis adjustment creates a perfectly flat video wall installation.

Easy to order

Use starter mounts and extender mounts to build your video wall. Starter mounts form the base of your wall. They're available in three sizes to hold two, three or four display panels and come in a set of two rails. Next, add extender mounts (also designed to hold two, three or four displays) to achieve the desired height of your video wall. Download the "How to Order" tip sheet. Helpful hint: The last digit of the part number indicates how many display panels the mount will hold. For example, DVM27U4 holds four panels. The extender DVM27U3E holds 3 panels.

Product Features:

- * Easy to Specify Easy to Order Easy to Install
- "Highly adaptable & stockable
- Sized for interlocking dvLED panels
- * Floating button-capture technology is compatible with most panels currently on the market
- Experience a consistent installation process every time with universal mounting hardware
- " Scalable & versatile
- Accurate alignment of panels to compensate for uneven installation surfaces with 3-axis adjustments (X-Y-Z axis)
- Double Depth Adjustment: macro and microadjustments create flawlessly flat video walls
- Independent Column Adjustment for perfectly level installations

Specifications

Dimensions &	Lateral Shift	1.71 cm (0.7 in)
Measurements	Manual Height Adjustment	50.8 mm (2 in)
	Minimum Depth	5.08 cm (2 in)
	Number of Panels	2
	Size	250/500/750/1000mm Class
	Typical Screen Size	500mm-tall dvLED Panels
	Wall Stud Compatibility	Meant for plywood- reinforced walls
	Weight Capacity	250 lbs (113.4 kg)
Characteristics &	Accessory Type	InstallationMounting Brackets
Features	Adjustability	FixedHeight AdjustableLateral ShiftMicro-Adjustable
	Adjustments	.625"
	Application	Wall
	Color	Black
	Orientation	Landscape or Portrait
	Product Type	Starter
	Solution Type	Universal
	Special Features	LED Video WallModularMulti-DisplaySecurityStacked
	TAA Compliant	Yes

Certifications &	Certifications	TAA
Warranties		

Source: https://www.legrandav.com/products/mounts/display-tv-mounts/tiled-universal-series-dvled-wall-mounts/dvm0500u2