logitech

Logitech Rally Bar

Brand : Logitech

Product name : Rally Bar

Product code: 991-000423

Logitech Rally Bar
Logitech Rally Bar. HD type: 4K Ultra HD, Supported video modes: 576p, 720p, 900p, 1440p, 2160p,
Maximum frame rate: 30 fps. Ethernet LAN, Wi-Fi. Display: IPS, Display diagonal: 25.6 cm (10.1"),
Display resolution: 1280 x 800 pixels. Product colour: Graphite

Performance

Product colour *	Graphite
Pan range	-25 - 25°
Tilt angle range	-15 - 15°
PTZ control	✔

Video

HD type *	4K Ultra HD
Supported video modes	576p, 720p, 900p, 1440p, 2160p
Maximum frame rate	30 fps

Audio

Built-in speaker(s)	✔
Output level	92/99 dB
Line-out impedance	4 Ω
Output voltage Total Harmonic Distortion (THD)	2%
Audio beamforming	✔
Noise reduction	✔
Echo cancellation	✔
RMS rated power	8 W
Microphone pick-up range	4.5 m
Sample rates	0 - 48 kHz

Ports & interfaces

HDMI ports quantity	3
HDMI output ports quantity	2
HDMI input ports quantity	1
USB connector type	USB Type-A, USB Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1
DC-in jack	✔

Interface module

Interface module RJ-45 ports quantity	1

Network

Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Supported network protocols	IPv4, IPv6
Security algorithms	128-bit AES

Microphone

Microphone direction type	Omnidirectional
Sound pressure level (max)	90 dB
Number of microphones	6

Features

Telepresence *	✗
Motion sensor	✔
Cable lock slot	✔
Cable lock slot type	Kensington

Logistics data

Master (outer) case gross weight	13 kg
Master (outer) case length	1013 mm
Master (outer) case width	270 mm
Master (outer) case height	327 mm
Harmonized System (HS) code	85176990

Battery

Battery capacity	0.675 Wh

Computer system

Windows operating systems supported	✔
Mac operating systems supported	MacOS

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 95%
Storage temperature (T-T)	-40 - 70 °C

Power

Power source type	AC
AC input voltage	100 - 240 V
Current	4.754 A
DC input voltage	19 V
Battery technology	Lithium
Battery capacity	220 mAh
Number of batteries supported	1
Power plug type	Type G

Weight & dimensions

Interface module dimensions (W x D x H)	246.2 x 171.3 x 56.1 mm
Interface module weight	1 kg
Width	910 mm
Depth	160 mm

Camera

Horizontal field of view	82.1°
Vertical field of view	52.2°
Diagonal field of view	90°
Remote control interface	Bluetooth

Display

Display	IPS
Display diagonal	25.6 cm (10.1")
Display resolution	1280 x 800 pixels
Contrast ratio (typical)	1000:1
Touchscreen	✔
Touchscreen type	Capacitive
Viewing angle, horizontal	85°
Viewing angle, vertical	85°
Display brightness	400 cd/m²
Oleophobic coating	✔

Microphone

Microphone sensitivity	-36 dB
Microphone frequency	90 - 16000 Hz

Weight & dimensions

Height	164 mm
Weight	7.08 kg
Package width	264 mm
Package depth	1007 mm
Package height	314 mm
Package weight	13 kg

Packaging content

Cables included	AC, DC, HDMI, USB Type-A to USB Type-C
Power cable length	2.5 m
HDMI cable length	2 m
Mounting kit	✔
Remote control included	✔
Camera included	✔
Quick start guide	✔
Packaging content	{loc-value}

5099206102200