POLY OBi VVX 350 6-Line IP Phone and PoE-enabled with Power Supply

Brand : POLY

Product name : OBi VVX 350 6-Line IP Phone and PoE-enabled with Power Supply

Product code: 89K70AA

- Hear every nuance on the VVX 350 with Poly HD Voice technology. And reduce distracting background noise with Poly Acoustic Fence technology.
- IT will appreciate zero-touch provisioning and web-based management capabilities that take the headache out of telephony deployment and support.
- Your phones stay cleaner for longer with integrated Microban® antimicrobial product protection [1] actively reducing the growth of bacteria 24/7.
OBi VVX 350 6-Line IP Phone and PoE-enabled with Power Supply

POLY OBi VVX 350 6-Line IP Phone and PoE-enabled with Power Supply:

Sound your best
Welcome to the big leagues with this high-quality, color, six-line business IP phone that gets the job done. For high-volume call environments that demand reliability, the Poly VVX 350 desk phone won't let you down.

Design

Product type *	IP Phone
Handset type	Wired handset
Product colour *	Black

Phone features

Lines quantity *	6 lines
Call waiting	✔
Distinctive ring	✔
Speed dialling	✔
Call hold	✔
Call forwarding	✔
Conference call	✔
Redialing	✔
Do not disturb function	✔
Call transfer	✔

Display

Display	LED
Display diagonal	8.89 cm (3.5")
Display resolution	320 x 240 pixels
Touchscreen *	✘

Audio

Speakerphone *	✔
Voice codecs	G.711, G.722, G.722.1, G.729ab, iLBC
Voice activity detection	✔
Comfort noise generation (CNG)	✔

Network

Ethernet LAN *	✔
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Security algorithms	802.1x RADIUS, HTTPS, TLS

Network

Syslog	✔

Technical details

Warranty period	1 year(s)

Ports & interfaces

USB 2.0 ports quantity	2
Ethernet LAN (RJ-45) ports	2

Certificates

Sustainability certificates	ENERGY STAR
Safety	UL 60950-1/62368-1, CE Mark, CAN/CSA C22.2 No 60950-1/62368-1-1, EN 60950-1/62368-1, IEC 60950-1/62368-1, AS/NZS 60950-1
Certification	FCC Part 15 (CFR 47) Class B ICES-003 Class B EN55032 Class B CISPR32 Class B VCCI Class B EN55024 EN61000-3-2; EN61000-3-3 NZ Telepermit Korea KCC3 UAE TRA Russia CU3 Brazil ANATEL3 Australia RCM South Africa ICASA3 Saudi Arabia CITC China CCC3 RoHS Complian TAA

Power

Power over Ethernet (PoE) *	✔
AC adapter output voltage	5 V
AC adapter output current	3 A

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-40 - 70 °C

Weight & dimensions

Width	233 mm
Depth	62 mm
Height	262 mm
Weight	1.04 kg

Packaging content	
Number of handles included *	1 pc(s)
AC adapter included	✔

0196188605004

196188605004

0196188605332

196188605332

0196188605196

196188605196