

Eaton 93PX15KIRTN

Catalog Number: 93PX15KIRTN

Eaton 93PX 15 kW RT9U Netpack. Includes 15 kW PM, 1 set of EBM, Network card and rail kits.

General Specifications



Product Name

Eaton 93PX UPS

Catalog Number

93PX15KIRTN

Product Length/Depth

820 mm

Product Height

128 mm

Product Width

600 mm

Product Weight

157.9 kg

Compliances

CE Marked

RoHS Compliant

CB

Certifications

IEC/EN 62040-2

IEC/EN 62040-1

EN 62040-3

Manufactured in a plant certified to ISO 9001 and ISO 14001 management system standards

EAN

6430070723952

Model Code

Eaton 93PX 15 kW RT9U Netpack



Powering Business Worldwide

Type

UPS

Audible alarms

Yes

Auto shutdown function

Yes

Internal battery included

Yes

User replaceable batteries

No

Battery charger type

ABM technology

External battery connection

Hardwired

Color

Black

Communication

USB port (HID compliant)

Serial port (RS232)

Mini terminal block for
remote On/Off

Mini-terminal block for
remote power off

Dry contacts (4 outputs,
relay, DB9)

DB15 for parallel operation

Construction type

482.6 mm (19 inch) device

Efficiency (eco-mode)

99 %

Improved efficiency mode

ESS

Number of communication slots

1

Feed type

AC

Form factor

Rack/tower

Hot-swappable power modules

No

Input connection

Fixed connection

Input nominal voltage

380Y/220V nominal (400V/230V, 415Y/240V)

Number Of Output Connections C13

0

Number Of Output Connections C19

0

Number of output connections fixed connection

1

Output frequency

50 Hz (50/60 Hz programmable)

Output power factor

1

Overall efficiency

0.96 %

Package contents

- UPS
- EBM
- Network card
- Rail kit (x3)
- Quickstart guide
- Safety instructions

Parallelable

Parallel for capacity and redundancy

Number of parallel units

3

Phase (input)

3

Phase (output)

3

Potential free switch contact

No

Rack size

9U

Runtime graph

[View runtime graph](#)

Snmp

Yes

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Topology

Online

kVA rating

15 kVA

Wattage

15 kW

Number Of Output Connections With Protective Contact (Schuko)

0

Application

Data center/ facility/IT

Output effective power

15000 W

Transition time for full load

0 s

Efficiency (improved efficiency mode)

99 %

Voltage distortion output (linear load) - max

1 %

Integrated functionality

Network Mangement

Communication interface

USB

RS232

Input frequency - min

50 Hz

Input frequency - max

60 Hz

Input voltage - min

220 V

Input voltage - max

415 V

Output voltage - min

220 V

Output voltage - max

415 V

Secondary Frequency Min

50 Hz

Secondary Frequency Max

60 Hz

Output apparent power

15000 VA

Primary frequency - max

60 Hz

Primary frequency - min

50 Hz

Runtime at half load

16 min

Runtime at full load

3 min

Mounting Method

Tower

Rackmount

Number of output connections French standard (Type E)

0

Power consumption

120



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia