## **PHILIPS**

## Philips P Line 329P1H/00 LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black

Brand : Philips Product family: P Line Product code: 329P1H/00

Product name: 329P1H/00

Brilliance 329P1H LCD monitor with USB-C docking

Philips P Line 329P1H/00 LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black:

Philips USB-C docking display for a comprehensive solution. View UltraClear 4K UHD and re-charge a laptop up to 90 W at the same time with a single USB-C cable. The pop-up webcam delivers performance and convenience.

Philips P Line 329P1H/00. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal:  $178^{\circ}$ , Viewing angle, vertical:  $178^{\circ}$ . Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black





| Display                               |                       | Ergonomics   |  |
|---------------------------------------|-----------------------|--|--|
| Display diagonal *                    | 80 cm (31.5")         | Height adjustment *  | <b>✓</b>   |
| Display resolution *                  | 3840 x 2160 pixels    | Height adjustment  | 18 cm  |
| HD type *                             | 4K Ultra HD           | Pivot  | /  |
| Native aspect ratio *                 | 16:9                  | Pivot angle  | -90 - 90°  |
| Display technology *                  | LED                   | Swivelling   | 1  |
| Panel type *                          | IPS                   | Swivel angle range   | -180 - 180°  |
| Backlight type                        | W-LED                 | Tilt adjustment  | ✓  |
| Touchscreen *                         | ×                     | •  | -5 - 25°   |
| Display brightness (typical)          | 350 cd/m <sup>2</sup> | Tilt angle range   |  |
| Response time *                       | 4 ms                  | On Screen Display (OSD)  | <b>✓</b>   |
| Anti-glare screen                     | ✓                     | On Screen Display (OSD) languages                              | Simplified Chinese, Traditional<br>Chinese, Czech, German, Dutch,<br>English, Spanish, Finnish, French,<br>Greek, Hungarian, Italian, Japanese,<br>Korean, Polish, Portuguese, Russian,<br>Swedish, Turkish, Ukrainian |
| Screen shape *                        | Flat                  |  |  |
| Aspect ratio                          | 16:9                  | On Screen Display (OSD) languages                              |  |
| Contrast ratio (typical) *            | 1000:1                |  |  |
| Contrast ratio (dynamic)              | 50000000:1            | Plug and Play  | ✓  |
| Dynamic contrast ratio marketing name | SmartContrast         | LED indicators   | Operation, Stand-by  |
| Maximum refresh rate *                | 60 Hz                 | Power  |  |
| Viewing angle, horizontal             | 178°                  | Energy efficiency class (SDR) *                                | G  |
| Viewing angle, vertical               | 178°                  | Energy consumption (SDR) per 1000                              | 40 kWh   |
| Display number of colours *           | 1.07 billion colours  | hours *  | 40 KWII  |
| Pixel pitch                           | 0.18159 x 0.18159 mm  | Power consumption (typical) *                                  | 31.8 W   |
| Pixel density                         | 140 ppi               | Power consumption (standby) *                                  | 0.3 W  |
| Horizontal scan range                 | 30 - 140 kHz          | Power consumption (PowerSave)                                  | 26.8 W   |
| Vertical scan range                   | 23 - 75 Hz            | AC input voltage   | 100 - 240 V  |
| Viewable size, horizontal             | 69.7 cm               | AC input frequency   | 50 - 60 Hz   |
| Viewable size, vertical               | 39.2 cm               | Power supply type  | Internal   |
| Digital horizontal frequency          | 30 - 140 kHz          | Energy efficiency scale  | A to G   |
| Digital vertical frequency            | 23 - 75 Hz            | European Product Registry for<br>Energy Labelling (EPREL) code | 399162   |

| Display  |  | Operational conditions   |   |
|--|--|--|---|
| Display diagonal (metric)  | 80 cm                                      | Operating temperature (T-T)  | 0 - 40 °C   |
| DDC/CI   | ✓  | Storage temperature (T-T)  | -20 - 60 °C   |
| Haze rate  | 25%  | Operating relative humidity (H-H)  | 20 - 80%  |
| Surface hardness   | 3H   | Operating altitude   | 0 - 3658 m  |
| Colour gamut standard  | sRGB                                       | Non-operating altitude   | 0 - 12192 m   |
| Colour gamut   | 117%                                       | Weight & dimensions  |   |
| sRGB coverage (typical)  | 128%                                       | Width (with stand)   | 714 mm  |
| NTSC coverage (typical)  | 117%                                       | Depth (with stand)   | 280 mm  |
| Adobe RGB coverage   | 89%  | Height (with stand)  | 649 mm  |
| Display sRGB   | <b>✓</b>                                   | Weight (with stand)  | 12.2 kg   |
| Performance  |  | Width (without stand)  | 714 mm  |
| NVIDIA G-SYNC *  | ×  | Depth (without stand)  | 62 mm   |
| AMD FreeSync *   | ×  | Height (without stand)   | 422 mm  |
| VESA Adaptive Sync support   | 1  | Weight (without stand)   | 8.19 kg   |
| Component video sync   | Separate sync                              | Packaging data   |   |
| •  | ✓  | Package width  | 930 mm  |
| Flicker-free technology  |  | Package depth  | 186 mm  |
| Low Blue Light technology  | ✓  | Package height   | 563 mm  |
| Multimedia   |  | Package weight   | 15.5 kg   |
| Number of speakers   | 2  | Package type   | Box   |
| RMS rated power  | 10 W                                       | Packaging content  |   |
| Built-in speaker(s) *  | ✓  | Stand included   | <b>✓</b>  |
| Megapixel (approx.)  | 2 MP                                       | Cables included  |   |
| Built-in microphone  | ✓  | Manual   | HDMI, DisplayPort, USB Type-C, AC   |
| Built-in camera *  | <b>✓</b>                                   |  | Constant Combined   |
| Dociem   |  | Bundled software   | SmartControl  |
| Design   |  | Sustainability   |   |
| Market positioning *   | Home                                       | Sustainability certificates  | ENERGY STAR, TCO  |
| Product colour * Front bezel colour  | Black<br>Black                             | Doesn't contain  | PVC/BFR, Mercury  |
| Feet colour  | Black                                      | Other features   |   |
|  | Black                                      | HBR3 support   | ✓   |
| Ports & interfaces   |  | USB Power Delivery revision  | 3.0   |
|  |  | OSB TOWER BEHVERY TEVISION   | 5.0   |
| Built-in USB hub *   | ✓  | Exterior finish type   | Textured  |
| USB hub version  | 3.2 Gen 2 (3.1 Gen 2)                      | •  |   |
| USB hub version<br>USB upstream port type  | 3.2 Gen 2 (3.1 Gen 2)<br>USB Type-C        | Exterior finish type   | Textured  |
| USB hub version<br>USB upstream port type<br>Number of upstream ports  | 3.2 Gen 2 (3.1 Gen 2)                      | Exterior finish type<br>Recyclable packaging material  | Textured<br>100%  |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports  | 3.2 Gen 2 (3.1 Gen 2)<br>USB Type-C        | Exterior finish type Recyclable packaging material Heavy metals free   | Textured<br>100%<br>Hg (mercury)  |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity   | 3.2 Gen 2 (3.1 Gen 2)<br>USB Type-C<br>1   | Exterior finish type Recyclable packaging material Heavy metals free Light sensor  | Textured<br>100%<br>Hg (mercury)<br>✓   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports  | 3.2 Gen 2 (3.1 Gen 2)<br>USB Type-C<br>1   | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode   | Textured 100% Hg (mercury)  ✓   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate  | 3.2 Gen 2 (3.1 Gen 2)<br>USB Type-C<br>1   | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode  | Textured 100% Hg (mercury)  ✓ ✓ 93 - 105%   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1         | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity   | Textured 100% Hg (mercury)  ✓   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD)   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement   | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE  |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4  90 W | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity   | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI *  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement Regulatory Approvals  | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU ROHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement   | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement Regulatory Approvals Delta E  | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU ROHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates  | Textured 100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2  RoHS  |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF)  | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2  RoHS 70000 h   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates  | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2  RoHS 70000 h 10,100,1000 Mbit/s  |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2  RoHS 70000 h 10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC,   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates  | Textured  100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, CE Mark, FCC Class B,                                       |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  Network   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification   | Textured 100%  Hg (mercury)  ✓  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified 2  RoHS 70000 h 10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC,   |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification  Recycling data   | Textured  100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE  Mark; FCC Class B; ICES-003; TUV  Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  Network   | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification  Recycling data Post-consumer recycled plastic                | Textured  100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, CE Mark, FCC Class B,                                       |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  Network Ethernet LAN                              | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification  Recycling data   | Textured  100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE  Mark; FCC Class B; ICES-003; TUV  Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  Network Ethernet LAN  Ergonomics                  | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification  Recycling data Post-consumer recycled plastic                | Textured  100%  Hg (mercury)  ✓  93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE  Mark; FCC Class B; ICES-003; TUV  Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s  ✓  UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU ROHS, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified |
| USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version  Network  Ethernet LAN  Ergonomics VESA mounting * | 3.2 Gen 2 (3.1 Gen 2) USB Type-C 1 4       | Exterior finish type Recyclable packaging material Heavy metals free Light sensor EasyRead mode LowBlue mode Philips SmartUniformity Picture enhancement  Regulatory Approvals  Delta E Compliance certificates Mean time between failures (MTBF) Ethernet LAN data rates Wake-on-LAN  Certification  Recycling data Post-consumer recycled plastic Logistics data | Textured  100%  Hg (mercury)    93 - 105%  SmartImage  UKRAINIAN; cETLus; CB; TUV/GS;  TUV Ergo; CU-EAC; EAEU RoHS; CE  Mark; FCC Class B; ICES-003; TUV  Eye Comfort certified  2  RoHS  70000 h  10,100,1000 Mbit/s    UKRAINIAN, EPA, cETLus, CB,  TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified |

| _     |      |        |
|-------|------|--------|
| Fra   | nnn  | mics   |
| L · y | 0110 | 111103 |

Cable lock slot type

Kensington





8712581768058

0609585253902



609585253902

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.