



Arm and Disarm in Seconds



Notifies You of Break-Ins



100° Motion Coverage



No Hidden Costs



Protect Your Entire Home



Arm and Disarm Remotely

Product Specifications



Entry Sensor	
Battery	CR123A Battery
MCU	CC1310
Certification	FCC, CE, CP65
Dimensions	Sensor: 2.91 x 1.10 x 0.86 in (74 x 28 x 22 mm)
	Magnet: 1.37 x 0.57 x 0.47 in (35 x 14.5 x 12 mm)
Weight	2.36 oz (67 g)
Operating Temperature	14°F to 122°F (-10°C to 50°C)



Motion Sensor	
Battery	CR123A Battery
MCU	CC1310
Certification	FCC, CE, CP6
Dimensions	2.21 x 2.21 x 0.86 in (56.2 x 56.2 x 22 mm)
Weight	2.46 oz (70 g)
Operating Temperatures	14°F to 122°F (-10°C to 50°C)



Keypad	
Battery	2,600mAh (Up to 180 days on one charge)
MCU	CC1312
Certification	FCC, CE, CP65
Dimensions	4.92 x 4.82 x 1.09 in (125.1 x 123.3 x 27.9 mm)
Weight	5.29 oz (150 g)
Operating Temperature	14°F to 122°F (-10°C to 50°C)



HomeBase	
Power Requirement	Input: 12V 2A Output: 5V 2A
Wi-Fi	802.11b/g/n
Sub 1G Connection	868MHz / 915MHz / 920MHz
EMMC	16GB
Operating Temperatures	14°F to 122°F (-10°C to 50°C)

