

Epson EB-L775U data projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) Black

Brand : Epson

Product code: V11HA96180

Product name : EB-L775U



4KE display solution

Epson EB-L775U. Projector brightness: 7000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video colour modes: Cinema, DICOM simulation mode, Dynamic, Multi-projection, Natural, Presentation. Serial interface type: RS-232C

Projector		Storage	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Card reader integrated *	✗
Projector brightness *	7000 ANSI lumens	Features	
Projection technology *	3LCD	Interactive *	✗
Projector native resolution *	WUXGA (1920x1200)	Noise level (economic mode)	27 dB
Contrast ratio (typical) *	2500000:1	Noise level *	37 dB
Native aspect ratio *	16:10	High Dynamic Range (HDR) supported	✓
Number of colours	1.07 billion colours	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Keystone correction, horizontal	-30 - 30°	Multimedia	
Keystone correction, vertical	-30 - 30°	Built-in speaker(s) *	✓
Light source		RMS rated power	10 W
Light source type *	Laser	Design	
Service life of light source *	20000 h	Market positioning *	Education
Service life of light source (economic mode)	30000 h	Product colour *	Black
Lens system		Placement	Ceiling, Desktop
Focus *	Manual	Cable lock slot	✓
Focal length range	20 - 31.8 mm	Cable lock slot type	Kensington
Aperture range (F-F)	1.5 - 1.7	Power	
Zoom capability	✓	Power source *	AC
Zoom type	Manual	Power consumption (typical) *	300 W
Throw ratio	1.35 - 2.20:1	Power consumption (standby) *	0.5 W
Video		Power consumption (max)	366 W
Analog signal format system *	Not supported	Power consumption (economy mode)	277 W
Full HD *	✓	AC input frequency	50/60 Hz
3D *	✗	AC adapter output voltage	100 - 240 V
Video colour modes	Cinema, DICOM simulation mode, Dynamic, Multi-projection, Natural, Presentation	Operational conditions	
Ports & interfaces		Storage temperature (T-T)	-10 - 60 °C
HDBaseT port	✓	Operating relative humidity (H-H)	20 - 80%
USB 2.0 ports quantity	2	Storage relative humidity (H-H)	10 - 90%
USB 2.0 Type-A ports quantity	1	Weight & dimensions	
USB 2.0 Type-B ports quantity	1	Width	440 mm
Serial interface type *	RS-232C	Depth	304 mm
HDMI ports quantity *	3	Height	122 mm
DVI port *	✗		

Network		Weight & dimensions	
Ethernet LAN *	✗	Weight *	8.5 kg
Wi-Fi *	✓	Packaging content	
		Remote control included *	✓
		Batteries included	✓



8715946712963

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-DEC-2024. Prints or copies of Information are only valid on the printed Publication date