



LG 65US662H9ZC 165.1 cm (65") 4K Ultra HD Wi-Fi Black

Brand : LG

Product code: 65US662H9ZC.AEU

Product name : 65US662H9ZC

- Pro:Centric Hotel Management Solution
- Voice Recognition
- Quick Menu
- LG Smart Hotel TV with Effective Content Management
- Pro:Centric Direct
- More Innovative LG webOS 5.0

65" 4K UHD Hotel TV 3840x2160, HDR10 Pro / HDR Dolby Vision / HLG, USB Cloning, HDMI, DA Out RS-232C RJ45, webOS 5.0

LG 65US662H9ZC. Display diagonal: 165.1 cm (65"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Screen shape: Flat, Native aspect ratio: 16:9. Digital signal format system: DVB-C, DVB-S2, DVB-T2. Wi-Fi, Ethernet LAN. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	165.1 cm (65")	PC in (D-Sub) *	✓
HD type *	4K Ultra HD	Ethernet LAN (RJ-45) ports	1
Screen shape *	Flat	USB 2.0 ports quantity *	2
Native aspect ratio *	16:9	Digital audio optical out	1
Native refresh rate	60 Hz	Headphone outputs	1
Display resolution *	3840 x 2160 pixels	RS-232C ports	1
Display diagonal (metric)	163.9 cm	RF ports quantity	2
TV tuner		Common interface (CI) *	✓
Tuner type *	Analog & digital	HDMI ports quantity *	3
Analog signal format system *	PAL	Management features	
Digital signal format system *	DVB-C, DVB-S2, DVB-T2	Hotel mode	✓
Smart TV		Power	
Operating system installed *	WebOS	Power consumption (typical) *	165 W
Operating system version	5.0	Power consumption (standby) *	0.5 W
Audio		Power consumption (max)	191 W
Number of speakers *	2	Energy efficiency class (SDR) *	G
RMS rated power *	20 W	Energy efficiency class (HDR) *	G
Network		Energy consumption (SDR) per 1000 hours *	135 kWh
Wi-Fi *	✓	Energy consumption (HDR) per 1000 hours *	149 kWh
Wi-Fi standards	Wi-Fi 5 (802.11ac)	AC input voltage	100 - 240 V
Bluetooth *	✓	AC input frequency	50 - 60 Hz
Ethernet LAN *	✓	Weight & dimensions	
Web browser	✓	Width (without stand)	1463 mm
Design		Depth (without stand)	87.8 mm
Product colour *	Black	Height (without stand)	850 mm
VESA mounting *	✓	Weight (without stand)	21.3 kg
Panel mounting interface	300 x 300 mm	Packaging data	
Performance		Package width	1600 mm
High Dynamic Range (HDR) technology	High Dynamic Range 10 Pro (HDR10 Pro), Hybrid Log-Gamma (HLG)	Package depth	190 mm
High Dynamic Range (HDR) supported *	✓	Package height	970 mm
		Package weight	28.1 kg

Performance

Image gallery	✓
USB cloning	✓



8806091543660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-DEC-2024. Prints or copies of Information are only valid on the printed Publication date