



AOC Porsche PD49 LED display 124.5 cm (49") 5120 x 1440 pixels DQHD QDOLED Black

Brand : AOC

Product family: Porsche

Product code: PD49

Product name : PD49



Screen size (inch) 49, Panel resolution 5120x1440, Max Refresh rate 240 Hz, Panel type QD - OLED, USB-C connectivity USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 90 W), HDMI HDMI 2.1 x 2, DisplayPort DisplayPort 1.4 x 1, Sync technology (VRR) Freesync Premium Pro
 AOC Porsche PD49. Display diagonal: 124.5 cm (49"), Display resolution: 5120 x 1440 pixels, HD type: DQHD, Display technology: QDOLED, Response time: 0.03 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	124.5 cm (49")	USB Power Delivery up to	90 W
Display resolution *	5120 x 1440 pixels	HDMI *	✓
HD type *	DQHD	HDMI ports quantity	2
Native aspect ratio *	32:9	HDMI version	2.1
Display technology *	QDOLED	DisplayPorts quantity	1
Panel type *	OLED	DisplayPort version	1.4
LED backlight	✓	Headphone out *	✓
Backlight type	QD	Headphone outputs	1
Touchscreen *	✗	Headphone connectivity	3.5 mm
Display brightness (typical)	1000 cd/m ²	Built-in KVM switch	✓
Response time	0.03 ms	KVM switch ports quantity	1
Anti-glare screen	✓	HDCP	✓
Screen shape *	Curved	HDCP version	2.2
Screen curvature rating	1800R	AC (power) in	✓
Contrast ratio (typical) *	1500000:1	Ergonomics	
Contrast ratio (dynamic)	80000000:1	VESA mounting *	✓
Maximum refresh rate *	240 Hz	Panel mounting interface	100 x 100 mm
Viewing angle, horizontal	178°	Cable lock slot *	✓
Viewing angle, vertical	178°	Cable lock slot type	Kensington
Display number of colours *	1.07 billion colours	Height adjustment *	✓
Pixel pitch	0.233 x 0.233 mm	Height adjustment	13 cm
Pixel density	108.5 ppi	Pivot	✗
Horizontal scan range	30 - 390 kHz	Swivelling	✓
Vertical scan range	48 - 240 Hz	Swivel angle range	-20 - 20°
Viewable size, horizontal	119.7 cm	Tilt adjustment	✓
Viewable size, vertical	33.9 cm	Tilt angle range	-3 - 13°
Display diagonal (metric)	124 cm	Picture-in-Picture	✓
High Dynamic Range (HDR) supported	✓	On Screen Display (OSD)	✓
High Dynamic Range (HDR) technology	DisplayHDR 400 True Black, High Dynamic Range 10 (HDR10)	Plug and Play	✓
DDC/CI	✓	LED indicators	Operation, Stand-by
Haze rate	25%	Power	
Surface hardness	2H	Power consumption (typical) *	130 W
sRGB coverage (typical)	151.6%	Power consumption (standby) *	0.5 W
NTSC coverage (typical)	125.9%	Power consumption (max)	330 W

Display		Power	
Adobe RGB coverage	123.7%	Power consumption (off)	0.3 W
BT.2020 coverage	83.8%	AC input voltage	100 - 240 V
Performance		AC input frequency	50/60 Hz
Fast charging	✓	Input current	4.5 A
Fast charging technology	Power Delivery 3.0	Power supply type	Internal
VESA Adaptive Sync support	✓	Operational conditions	
Flicker-free technology	✓	Operating temperature (T-T)	0 - 40 °C
Low input lag	✓	Storage temperature (T-T)	-25 - 55 °C
FPS counter	✓	Operating relative humidity (H-H)	10 - 85%
Dial point	✓	Storage relative humidity (H-H)	5 - 93%
Shadow control	✓	Operating altitude	0 - 5000 m
Game mode	✓	Non-operating altitude	0 - 12192 m
Compatible operating systems	Windows 8.1/10/11, MacOS	Packaging content	
Multimedia		Stand included	✓
Built-in speaker(s) *	✓	Cables included	AC
Built-in camera *	✗	Screws included	✓
Number of speakers	2	Weight & dimensions	
RMS rated power	16 W	Width (with stand)	1191.8 mm
Audio decoders	DTS	Depth (with stand)	388.3 mm
Design		Height (with stand)	561.5 mm
Market positioning *	Gaming	Weight (with stand)	15.8 kg
Product colour *	Black	Width (without stand)	1191.8 mm
Frameless design	✓	Depth (without stand)	160.7 mm
Front bezel colour	Black	Height (without stand)	373.8 mm
Ports & interfaces		Weight (without stand)	11.2 kg
Built-in USB hub *	✓	Packaging data	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package width	1310 mm
Number of USB Type-C upstream ports quantity	1	Package depth	506 mm
USB Type-A downstream ports quantity	4	Package height	565 mm
USB Type-C downstream ports quantity	1	Package weight	25.3 kg
USB Power Delivery	✓	Other features	
		DCI-P3 coverage	115%
		Picture-by-Picture (PbP)	✓
		Bezel thickness type	Frameless



4056487052403



6973985230370

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.