

## FFRE4120SW

### ELECTRIC DRYER

6.7 CU.FT. D.O.E.



#### AVAILABLE COLORS



#### PRODUCT DIMENSIONS

Height	44-1/4"
Width	27"
Depth	30-13/16"

#### MORE EASY-TO-USE FEATURES

##### 5 Dryness Levels

Includes: Air Dry, Ultra Low, Low, Medium, and High.

##### Anti-Wrinkle

Anti-Wrinkle Option helps reduce wrinkles.

##### Electronic Controls

Easy-to-use electronic controls with digital readout and cycle status lights.

##### Reversible Door

Offers versatile installation options.

### SIGNATURE FEATURES

#### Large Capacity

Fit more in every load.

#### Quick Dry Cycle

Dries clothes fast.

#### 10 Dry Cycles

Features 10 dry cycles to meet all of your drying needs such as Bulky, Casual and Sanitize.

#### Multiple Cycle Options

Personalize your drying with options such as My Cycle and Eco Dry.

# FFRE4120SW ELECTRIC DRYER

FRIGIDAIRE

6.7 CU.FT. D.O.E.

## FEATURES

Total Capacity D.O.E. (Cu.Ft.)	6.7
Controls	Digital
Dryer Drum Interior	Stainless Steel
DrySense™ Technology	Yes
Wrinkle Release Technology	Yes
Moisture Sensor	Yes
Estimated Time Remaining	Yes
Cycle Status Lights	Yes
Cycle Signal	Chime
Cycle Signal "On/Off"	Yes
Start/Pause/Cancel Knobs	Yes
Delay Start	Yes
Tumble Speed (RPM)	50
Reversible Door	Yes
Lint Screen	Yes
Adjustable Leveling Legs	4

## CYCLES

Dry Cycles	10
------------	----

## OPTIONS

Temperature Selections	4
Dryness Level Selections	5
Timed Dry	Yes



## SPECIFICATIONS

Maximum Exhaust Duct Length <sup>1</sup> (Ft.)	64
Power Supply Connection Location	Rear
Voltage Rating	120V/240V/60Hz
Connected Load (kW Rating) @ 240 Volts	5.4
Amps @ 240 Volts	24
Heating Element @ 240 Volts (Watts)	4,800
Shipping Weight (Approx.)	143 Lbs.

<sup>1</sup>Rigid metal duct preferred, semi-rigid optional and allow deductions for elbows and vents. Refer to Installation Guide on web for additional information.

## PRODUCT DIMENSIONS

A - Height	44-1/4"
B - Width	27"
C - Depth	30-13/16"
Depth with Door Open 90°	48-5/8"



**Note:** For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com](http://frigidaire.com).

Specifications subject to change. Accessories information available on the web at [frigidaire.com](http://frigidaire.com)

FRIGIDAIRE


USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • [frigidaire.com](http://frigidaire.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [frigidaire.ca](http://frigidaire.ca)

FFRE4120S 06/18  
© 2018 Electrolux Home Products, Inc.

# FFRE4120SW ELECTRIC DRYER

6.7 CU.FT. D.O.E.

FRIGIDAIRE



## Recess or Closet Installation

Dryer installation requires 1" minimum installation clearance on each side of unit and 6" minimum at back. To achieve 6" minimum rear clearance, dryer MUST use 90° quick-turn vent elbow. Closet installation requires 2" minimum clearance between front of unit and vented door. Door MUST be vented with 120 sq. in. minimum louvered opening, equally divided, located 3" from top and bottom of door. A louvered door with equivalent air openings for full-length of door is acceptable. Air openings MUST remain unobstructed with door installed. For additional installation details, refer to Product Installation Guide on web.

## INSTALLATION SPECIFICATIONS

- Product Shipping Weight (approx.) - 143 Lbs.
- Designed for HOME USE only, not recommended for commercial application.
- An electrical supply with grounded three-prong receptacle is required.
- Voltage Rating - 120V/240V/60Hz
- Single phase 3- or 4-wire cable, 240 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line. (Do not use same circuit as washer.)
- Connected Load (kW Rating) @ 240 Volts = 5.4kW
- Amps @ 240 Volts = 24 Amps
- Dryer MUST employ a 3-conductor NEMA 10-30 type SRDT or 4-conductor NEMA 14-30 type SRDT or ST (as required), rated at 240 volt AC minimum, 30 amp power supply cord marked for use with clothes dryers (not supplied).
- Grounding through neutral link prohibited in specific applications and certain locales, requiring use of 4-wire system. (For detailed electrical requirements, refer to Product Installation Guide on web.)
- Always consult local and national electric codes.
- Dryer installation requires 1" minimum installation clearance on each side of unit and 6" minimum at back. To achieve 6" minimum rear clearance, dryer MUST use 90° quick-turn vent elbow. Closet installation requires 2" minimum clearance between front of unit and vented door. Door MUST be vented with 120 sq. in. minimum louvered opening, equally divided, located 3" from

top and bottom of door. A louvered door with equivalent air openings for full-length of door is acceptable. Air openings MUST remain unobstructed with door installed. (For additional installation details, refer to Product Installation Guide on web.)

- Do NOT install in area exposed to dripping water or outdoor weather conditions; where gasoline or other flammables are kept or stored; or where dryer comes in contact with curtains, drapes or anything that will obstruct flow of combustion and ventilation air.
- For garage installation, dryer MUST be located minimum 18" above floor.
- Floor MUST be solid with 1" maximum slope. Do NOT install on carpeted surface.
- Dryer MUST exhaust to outside of building, NOT into any concealed space.
- Exhaust installation requires minimum 4"-diameter rigid or semi-rigid metal duct with approved, unobstructed vent hood having swing-out damper(s). If installing rigid metal duct (preferred), do not exceed MAXIMUM venting run length of 64 ft., allow deductions for elbows and vents. If installing semi-rigid metal duct, do not exceed MAXIMUM venting run length of 8 ft., always allow deductions for elbows and vents (Refer to Product Installation Guide on web for additional information). Do NOT use flexible plastic or metal foil duct and use shortest run possible.
- Leveling legs supplied to level dryer properly and reduce excessive noise and vibration.



FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidare.com  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidare.ca

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidare.com.

Specifications subject to change. Accessories information available on the web at frigidare.com

FFRE4120S 06/18

© 2018 Electrolux Home Products, Inc.

## FFTW4120SW

### TOP LOAD WASHER

4.1 CU. FT. D.O.E.



#### AVAILABLE COLORS



Classic White

#### PRODUCT DIMENSIONS

Height	44-1/4"
Width	27"
Depth	29"

#### MORE EASY-TO-USE FEATURES

##### 5 Soil Levels

Includes: Extra Heavy, Heavy, Medium, Light and Extra Light.

##### Stainless Steel Drum

The stainless steel drum with agitator offers durability with long-lasting performance.

##### Electronic Controls

Easy-to-use electronic controls with digital readout and cycle status lights.

##### Fabric Softener Dispenser

Conveniently add fabric softener at the beginning of the wash cycle.

### SIGNATURE FEATURES

#### Large Capacity

Fit more in every load.

#### Quick Wash Cycle

Washes clothes fast.

#### 12 Wash Cycles

Features 12 wash cycles to meet all of your washing needs such as Delicate, Hand Wash and Heavy Duty.

#### Multiple Cycle Options

Personalize your wash with options such as Favorite Cycle and Max Fill.

# FFTW4120SW TOP LOAD WASHER

FRIGIDAIRE

4.1 CU. FT. D.O.E.

## FEATURES

Washer Type	HE Top Load
Total Capacity D.O.E. (Cu.Ft.)	4.1
Controls	Digital
Washer Drum Interior	Stainless Steel
Framed Glass Window Lid	Yes
Suspension System	Hanging
Wash System	Agitator
Fresh Water Rinse	Yes
Estimated Time Remaining	Yes
Bleach Dispenser	Yes
Fabric Softener Dispenser	Yes
Cycle Status Lights	Yes
Cycle Signal	Yes
Cycle Signal "On/Off"	Yes
Control Lock	Yes
Start/Pause/Cancel Knobs	Yes
Delay Start	Up to 24 Hours
Agitate Speed (Stroke/Min.)	Variable
Spin Speed (Maximum RPM)	680
Adjustable Leveling Legs	2

## CYCLES

Wash Cycles	12
-------------	----

## OPTIONS

Water Temperature Selections	3
Water Levels	Automatic
Spin Speed Selections	Automatic
Soil Level Selections	5
Energy Saver Option	Yes



## SPECIFICATIONS

Power Supply Connection Location	Left Top Rear
Water Inlet Connection Location	Left Rear
Voltage Rating	120V/60Hz
Connected Load (kW Rating) @ 120 Volts <sup>1</sup>	0.4
Watts @ 120 Volts/ Amps @ 120 Volts	295/ 4.0
Minimum Circuit Required (Amps)	15
Shipping Weight (Approx.)	157 Lbs.

<sup>1</sup>For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

## PRODUCT DIMENSIONS

A - Height	44-1/4"
B - Width	27"
C - Depth	29"




**Note:** For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.com](http://frigidaire.com).

Specifications subject to change. Accessories information available on the web at [frigidaire.com](http://frigidaire.com)

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • [frigidaire.com](http://frigidaire.com)  
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • [frigidaire.ca](http://frigidaire.ca)

FFTW4120S 06/18  
© 2018 Electrolux Home Products, Inc.



### Recess or Closet Installation

Washer installation requires 1" minimum installation clearance on each side of unit and 6" minimum at back. To achieve 6" minimum rear clearance when installed with dryer, dryer MUST use 90° quick-turn vent elbow. Closet installation requires 2" minimum clearance between front of unit and vented door. Door MUST be vented with 120 sq. in. minimum louvered opening, equally divided, located 3" from top and bottom of door. A louvered door with equivalent air openings for full-length of door is acceptable. Air openings MUST remain unobstructed with door installed. For additional installation details, refer to Product Installation Guide on web.

## INSTALLATION SPECIFICATIONS

- Product Shipping Weight (approx.) - 157 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (ANSI/NFPA 70) and local codes & ordinances. (Do not use same circuit as dryer.)
- Voltage Rating - 120V/60 Hz
- Amps @ 120 Volts = 8.0 Amps
- Equipped with 120V 3-wire power supply cord, approx. 70-1/2" long.
- Always consult local and national electric & plumbing codes.
- To maximize detergent effectiveness, ambient temperature should never be below 60° F.
- Washer installation requires 1" minimum installation clearance on each side of unit and 6" minimum at back. To achieve 6" minimum rear clearance when installed with dryer, dryer MUST use 90° quick-turn vent elbow. Closet installation requires 2" minimum clearance between front of unit and vented door. Door MUST be vented with 120 sq. in. minimum louvered opening, equally divided, located 3" from top and bottom of door. A louvered door with equivalent air openings for full-length of door is acceptable. Air openings MUST remain unobstructed with door installed. (For additional installation details, refer to Product Installation Guide on web.)
- Do NOT install in area exposed to dripping water or outdoor weather conditions; or where gasoline or other flammables, including automobiles, are kept or stored.
- Floor MUST be solid with 1" maximum slope. To minimize vibration or movement, reinforcement of floor may be necessary. Do NOT install on carpeted surface.
- Leveling legs supplied to level unit properly and reduce excessive noise and vibration.
- H/C water faucets MUST be installed within 42" of washer's water inlet and MUST be 3/4" with threading for laundry hose connection to connect to 48" inlet hoses.
- Water pressure MUST be between 30 and 120 psi with NOT more than 10 psi pressure difference between hot and cold.
- Drain standpipe requires diameter of 1-1/4" min. and height of 39" min./96" max. above floor, capable of eliminating 17 gallons per minute. Attached 59" drain hose can reach 74"-high standpipe. For higher standpipe, optional Drain Hose Extension Kit available.

