

OM-D E-M10 Mark IV SHOOT. SHARE. INSPIRE.

You've started to enjoy photography. Shots from your cell phone aren't enough anymore, and you're looking to get to the next level. The OM-D E-M10 Mark IV is for you. This easy-to-use camera is perfect for developing your talent and skills. You'll find features for taking one amazing shot after another. Foolproof technology eliminates motion blur for super sharp, stunningly bright stills and video — even in dark locations. Take a self-portrait instantly and share it in seconds. Best of all, it weighs only a pound with the lens. You won't find a lighter, more portable camera. The E-M10 Mark IV. Take your photography further.

FEATURES:

- 20MP Image Sensor
- Shake-Free 5-Axis Image Stabilization
- 16 Art Filters
- 180° Flip Touch Screen
- Ultra HD 4K Video
- Built-In Wi-Fi
- Built-In Flash

AVAILABLE COLOR:



OM-D E-M10 Mark IV SPECIFICATIONS



NUMBER OF PIXELS	20.3 millions pixels, Aspect Ratio 4:3
IMAGE STABILIZATION	Built-in 5-axis sensor-shift IS for still photos & video
STABILIZATION PERFORMANCE	4.5 EV steps* *When using the M.ZUIKO DIGITAL ED 14-42mm F3.5-5.6 EZ Focal length: 42mm (35mm equivalent: 84mm)
VIEWFINDER	Electronic OLED viewfinder, Approx. 2.36M dots
REAR MONITOR	3.0-inch tilting* monitor (electrostatic capacitance touch panel), approx. 1037k dots (3:2) *Tilt type: Upward tilting: Up to approx. 80 degrees Downward tilting: Up to approx. 180 degrees (Selfie compatible)
FIELD OF VIEW / VIEWFINDER MAGNIFICATION	Approx. 100% / Approx. 1.23x
LIVE VIEW	Approx. 100% field of view exposure compenstation preview, WB adjustment preview, gradation preview, face detection preview (up to 8 faces)
AUTOFOCUS	121-point Contrast Detection AF
SHUTTER TYPE	Mechanical and electronic shutter 1/4000 - 60 sec., with 1/3 EV adjustment steps Live Bulb/Live Time: Max. 30 min. Live composite: Max. 3 hours Electronic first curtain shutter (Anti-shock mode): 1/320 - 60 sec Electronic shutter (Silent mode): 1/16000 - 60 sec
ART FILTERS	Pop ArtGrainy FilmGentle SepiaVintageSoft FocusPin HoleDramatic TonePartial ColorPale & Light ColorDioramaKey LineBleach BypassLight ToneCross ProcessWater ColorInstant Film
VIDEO RECORDING FORMAT	MOV D212 (MPEG-4AVC / H.264)
MODE / FRAME RATE / COMPRESSION METHOD	3840 × 2160 (4K) / 30p, 25p, 24p / IPB (approx. 102 Mbps) 1920 × 1080 (FHD) / 30p, 25p, 24p / IPB (SF, F, N) 1920 × 1080 (FHD) / 60p, 50p / IPB (SF, F, N) 1280 × 720 (HD) / 60p, 50p, 30p, 25p, 24p / IPB (SF, F, N)
HIGH SPEED MOVIE	1280 x 720 (HD) / 120fps, MOV
SEQUENTIAL SHOOTING MAXIMUM SPEED	S-AF: Approx. 15 fps* (IS ON/OFF) *When using the M.Zuiko Digital ED 14-42mm F3.5-5.6 EZ C-AF: Approx. 6.3 fps** (IS ON/OFF) **When using the M.Zuiko Digital ED 12-40mm f/2.8 PRO
WIRELESS CONNECTIVITY	Wi-Fi (802.11 b/g/n) & Bluetooth (Ver.4.2 Low Energy)
USB CHARGING	Built-in battery can be charged with USB * When the camera power is off * Performance varies depending on different USB devices
DIMENSIONS	W:121.7mm H:84.4mm D:49mm (based on CIPA standards)
WEIGHT	Approx. 383 g (with BLS-50 battery and Memory card, based on CIPA standards) Approx. 335 g (body only)

To learn more about Olympus & OM SYSTEM products, please visit https://explore.omsystem.com

*Specifications and appearances are subject to change without any notice or obligation on the part of the manufacturer. *The colors of products printed herein may differ from those of the actual products. *All other company and product names are registered trademarks and/or trademarks of their respective owners. *The date herein is as of July 2023. © 2023 OM Digital Solutions

