

FPA84 RP

Repeater Panel

The **FPA84 RP** repeater panel is a compact remote unit for Avani control panel. It repeats all the indications of FACP in standalone or as a network Panel. It is connected to **FPA84** control panel via an RS-485 communications link. The display parameters can be selected individually to suit the requirement of each remote area.



UL 864 9th Edition

Key Features

- Networkable
- 160 (40 × 4) character LCD display
- Event history storage with real-time clock
- Networkable using RS-485
- Programmable Form C relay for fire
- Extensive in-build transient protection
- Indicator test facility
- Common fire, supervisory and LED fault indication
- Rugged metal enclosure

TECHNICAL SPECIFICATIONS

OPERATING VOLTAGE	DC 24 V
QUIESCENT CURRENT	80 mA
ALARM CURRENT	130 mA
PROGRAMMABLE RELAY	1 × 2 A @ DC 30 V or 0.5 A @ AC 125 V
OPERATING TEMPERATURE	-0 °C ~ +49 °C
OPERATING HUMIDITY	93 % RH, non-condensing @ 32 °C
DIMENSIONS (H × W × D)	(300 × 350 × 90) mm
COLOUR	White, red, black powder coat
WEIGHT	5 kg
INGRESS PROTECTION RATING	IP-50

ORDER CODE Description

FPA84RP	Addressable repeater panel
---------	----------------------------

