

NB349

Wireless Interconnection Sounder strobe

NB349 wireless interconnectable sounder strobe can be used with NB580/NB590 wireless smoke alarm or NB839 hard-wired interconnection smoke alarms to alert people of fire risk detected by interconnected smoke alarms. NB349 do not require a mains supply and are suitable for general residential applications.

Key Features

- Interconnectable with NB590 wireless smoke alarm
- Interconnectable with remote controller for test and silence
- DC 1.5 V AA battery * 8
- Loud sounder output of 85 dB at 3 m
- Long-life strobe light
- Easy installation
- Low maintenance



TECHNICAL SPECIFICATIONS

OPERATING VOLTAGE	DC 1.5 V AA battery * 8
STANDBY CURRENT	≤15uA
ALARM CURRENT	120 mA
SOUNDER OUTPUT	85 dB @ 3 m
STROBE LIGHT FLASH RATE	≤ 2 s
STROBE LIGHT OUTPUT POWER	2.5 W
TERMINAL WIRING	0.4 mm ² ~ 2.5 mm ²
OPERATING TEMPERATURE	-10 °C ~ +50 °C
OPERATING HUMIDITY	0 % ~ 95 % RH, non-condensing
STORAGE TEMPERATURE	-25 °C ~ +80 °C
STORAGE HUMIDITY	0 % ~ 98 % RH, non-condensing
DIMENSIONS (H × W × D)	(120 × 80 × 42) mm
INGRESS PROTECTION RATING	IP-23

ORDER CODE

	Sounder	Strobe Light	Wireless
NB349-H	✓	✓	
NB349-W	✓	✓	✓

